



# APPLICATION GUIDE

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

															Application			
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
<b>Ford</b>																		
<b>E-Series Cutaway / Strip Chassis</b>																		
<b>Front E450</b>	2021-Current	5000	n/a	Cutaway, Strip	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS50F 5000	Front Suspension (requires Rear DS96FS3 kit)	X	X		X
	2021-Current	5000	n/a	Cutaway, Strip	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS50F-EC 5000	Front Suspension (requires Rear DS96FS3-EC kit)	X	X		X
	2021-Current	5000	n/a	Cutaway, Strip	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS50FTE 5000	Front Suspension (requires Rear DS96FS3-MTE kit). System is equipped with Tru-Earth Leveling™.				X
<b>REAR E350</b>	2021-Current	8500	n/a	Cutaway, Strip	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS85FS3 8500		X	X	X	
	2021-Current	8500	n/a	Cutaway	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS85FS3-BA 8500	Uses 10830-014 volume mounts on driver side (vol. under frame)		X		
	2021-Current	8500	n/a	Cutaway, Strip	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS85FS3-FR 8500	Telma Bus Kit				X
<b>REAR E450</b>	2021-Current	9600	n/a	Cutaway, Strip	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS96FS3 9600		X	X	X	
	2021-Current	9600	n/a	Cutaway	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS96FS3-BA 9600	Uses 10830-014 volume mounts on driver side (vol. under frame)		X		
	2021-Current	9600	n/a	Cutaway, Strip	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS96FS3-MTE 9600	(Requires FS50FTE Front Kit). Uses 10830-014 volume mounts, & larger struts. System is equipped with Tru-Earth Leveling™.				X
	2021-Current	9600	n/a	Cutaway, Strip	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS96FS3T 9600	Requires Front FS50F kit. Front kneels first				X
	2021-Current	9600	n/a	Cutaway, Strip	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS96FS3-EC 9600	Requires Front FS50F-EC kit. Front kneels first				X
	2021-Current	9600	n/a	Cutaway, Strip	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS96FS3-FR 9600	Telma Bus Kit				X
	2021-Current	9600	n/a	Cutaway, Strip	158, 176	100, 118	n/a	Any	Rear	n/a	n/a	No	DS96FS3-CLF 9600	Compatible with front suspension FS50F-EC				X
<b>REAR Arboc E450 Low Floor</b>	2021-Current	9600	n/a	Cutaway	SP	SP	n/a	Any	Rear	n/a	n/a	No	DS96FS3-ASF 9600	Special unit for Arboc Low Floor bus; Spirit of Freedom only; Front susp add on requires ECU that is rear kneel first.				X
													DS96FS3-ASM 9600	Special unit for Arboc Low Floor bus; Spirit of Mobility only; Requires front suspension FS50F. Front kneels first				X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
<b>F250 Pickup Stock Height</b>																	
Front F250 Pickup (4x4)	2020-Current	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS2P 6000	4x4 only; Front suspension with Dual Springs (Requires DS63FS2P-DS/DS63FS2P-SS rear suspension). Ford camper package requires kit to change to equivalent F-350 kit (DS72FS2P).	X		
													FS60FS2PE <sup>1</sup> 6000	<b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
Rear F250 SRW Pickup	2020-Current	6340	SRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS63FS2P-DS 6340	Removes spare tire. Volumes & power module mounted behind rear axle. Ford camper package requires kit to change to equivalent F-350 kit (DS72FS2P). <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
	2020-Current	6340	SRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS63FS2P-SS 6340	Long bed required. Volumes & power module mounted under cab & bed. MY23+ requires RF bed side step to be replaced (included in kit). Ford camper package requires kit to change to equivalent F-350 kit (DS72FS2P). <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		

<sup>1</sup>International export models have 0 psi precharge accumulators

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

														Application				
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
<b>F250 Pickup 2" Lift Kit</b>																		
Front F250 Pickup (4x4)	2020-2022	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS3P-L2 6000	4x4 only; Front suspension with Dual Springs (Requires DS63FS2P-L2DS/-L2SS rear suspension). Ford camper package requires kit to change to equivalent F-350 kit (DS72FS2P).	X			
													FS60FS3P-L2E <sup>1</sup> 6000		X			
	2023-Current	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS4P-L2 6000	<b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X			
													FS60FS4P-L2E <sup>1</sup> 6000		X			
Rear F250 SRW Pickup	2020-Current	6340	SRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS63FS2P-L2DS 6340	Removes spare tire. Volumes & power module mounted behind rear axle. Ford camper package requires kit to change to equivalent F-350 kit (DS72FS2P). <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X			
	2020-Current	6340	SRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS63FS2P-L2SS 6340	Long bed required. Volumes & power module mounted under cab & bed. MY23+ requires RF bed side step to be replaced (included in kit). Ford camper package requires kit to change to equivalent F-350 kit (DS72FS2P). <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X			

<sup>1</sup>International export models have 0 psi precharge accumulators

### LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
<b>F250 Pickup 4" Lift Kit</b>																	
Front F250 Pickup (4x4)	2020-2022	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS3P-L4 6000	4x4 only; Front suspension with Dual Springs (Requires DS63FS2P-L4DS rear suspension). Ford camper package requires kit to change to equivalent F-350 kit (DS72FS2P).	X		
													FS60FS3P-L4E <sup>1</sup> 6000		X		
	2023-Current	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS4P-L4 6000	<b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
													FS60FS4P-L4E <sup>1</sup> 6000		X		
Rear F250 SRW Pickup	2020-Current	6340	SRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS63FS2P-L4DS 6340	Removes spare tire. Volumes & power module mounted behind rear axle. Ford camper package requires kit to change to equivalent F-350 kit (DS72FS2P).	X		
													DS63FS2P-L4DSE <sup>1</sup> 6340		X		
<sup>1</sup> International export models have 0 psi precharge accumulators																	

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
<b>F350 Pickup Stock Height</b>																	
Front F350 Pickup (4x4)	2020-Current	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS2P 6000	4x4 only; Front suspension with Dual Springs (Requires DS72FS2P-DS/-DSE/-SS or DS103FS2P-SS rear suspension)	X		
													FS60FS2PE <sup>1</sup> 6000	<b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
Rear F350 SRW Pickup	2020-Current	7230	SRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS72FS2P-DS 7230	Removes spare tire. Volumes & power module mounted behind rear axle. Dual Springs.	X		
													DS72FS2P-DSE <sup>1</sup> 7230	<b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
													DS72FS2P-SS 7230	Long bed required. Volumes & power module mounted under cab & bed. MY23+ requires RF bed side step to be replaced (included in kit).	X		
Rear F350 DRW Pickup	2020-Current	10300	DRW Only	Any	Any	56	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-SS 10300	<b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		

<sup>1</sup>International export models have 0 psi precharge accumulators

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
<b>F350 Pickup 2" Lift Kit</b>																	
Front F350 Pickup (4x4)	2020-2022	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS3P-L2 6000	4x4 only; Front suspension with Dual Springs (Requires DS72FS2P-L2DS/-L2SS or DS103FS2P-L2DS/-L2SS rear suspension).	X		
													FS60FS3P-L2E <sup>1</sup> 6000		X		
	2023-Current	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS4P-L2 6000	<b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
													FS60FS4P-L2E <sup>1</sup> 6000		X		
Rear F350 SRW Pickup	2020-Current	7230	SRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS72FS2P-L2DS 7230	Removes spare tire. Volumes & power module mounted behind rear axle. <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
Rear F350 SRW Pickup	2020-Current	7230	SRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS72FS2P-L2SS 7230	Long bed required. Volumes & power module mounted under cab & bed. MY23+ requires RF bed side step to be replaced (included in kit). <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
Rear F350 DRW Pickup	2020-Current	10300	DRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-L2DS 10300	Removes spare tire. Volumes & power module mounted behind rear axle. <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
													DS103FS2P-L2DSE <sup>1</sup> 10300		X		
	2020-Current	10300	DRW Only	Any	Any	56	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-L2SS 10300	Long bed required. Volumes & power module mounted under cab & bed. MY23+ requires RF bed side step to be replaced (included in kit). <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		

<sup>1</sup>International export models have 0 psi precharge accumulators

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
<b>F350 Pickup 4" Lift Kit</b>																	
Front F350 Pickup (4x4)	2020-2022	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS3P-L4 6000	4x4 only; Front suspension with Dual Springs (Requires DS72FS2P-L4DS or DS103FS2P-L4DS rear suspension) <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
													FS60FS3P-L4E <sup>1</sup> 6000		X		
	2023-Current	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS4P-L4 6000	4x4 only; Front suspension with Dual Springs (Requires DS72FS2P-L4DS or DS103FS2P-L4DS rear suspension) <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
													FS60FS4P-L4E <sup>1</sup> 6000		X		
Rear F350 SRW Pickup	2020-Current	7230	SRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS72FS2P-L4DS 7230	Removes spare tire. Volumes & power module mounted behind rear axle. Dual Springs. <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		
													DS72FS2P-L4DSE <sup>1</sup> 7230		X		
Rear F350 DRW Pickup	2020-Current	10300	DRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-L4DS 10300		X		
	2020-Current	10300	DRW Only	Any	Any	56	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-L4SS 10300	Long bed required. Volumes & power module mounted under cab & bed. MY23+ requires RF bed side step to be replaced (included in kit). <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X		

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application			
															Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
<sup>1</sup> International export models have 0 psi precharge accumulators																		
<b>F350 Cab Chassis</b>																		
<b>FRONT F350 Cab Chassis 4x4 ONLY</b>	2020-Current	5990	Std. Track	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FP 6000	4x4 only; Front suspension (Requires DS103F4 or DS103F4F rear suspension; DS103F4F requires <b>13205</b> -4 Hose Routing Kit)	X	X	X	X
<b>REAR F350 4x2 Cab Chassis</b>	2017-Current	10300	Any	Reg	169	84	n/a	Any	Mid*, Rear	n/a	n/a	No	DS103F2 10300	* Mid ship fuel tank may require relocation of OEM DEF tank.	X	X		
	2017-Current	10300	Any	Reg	169	84	n/a	Any	Dual	n/a	n/a	No	DS103F2F 10300	Special unit for Frazer. PM mounted behind rear fuel tank.		X		
<b>REAR F350 4x4 Cab Chassis</b>	2017-Current	10300	Any	Reg	169	84	n/a	Any	Mid*, Rear	n/a	n/a	Yes	DS103F4 10300	* Mid ship fuel tank may require relocation of OEM DEF tank.	X	X		
	2017-Current	10300	Any	Reg	169	84	n/a	Any	Dual	n/a	n/a	Yes	DS103F4F 10300	Special unit for Frazer. PM mounted behind rear fuel tank.		X		

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

														Application				
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
	2017-Current	10300	Any	Reg	145 168	60	n/a	Diesel 6.7L	Mid*, Rear	n/a	n/a	Yes	DS103F4-DS60D 10300	* Mid ship fuel tank may require relocation of OEM DEF tank.	X	X		
<b>F450 Pickup Stock Height</b>																		
Front F450 Pickup (4x4 or 4x2)	2020-Current	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS2PW 6000	Front suspension with Dual Springs (Requires DS103FS2P-SS rear suspension) <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X			
													FS60FS2PWE <sup>1</sup> 6000		X			
Rear F450 Pickup	2020-Current	10300	DRW Only	Any	Any	56	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-SS 10300	Long bed required. Volumes & power module mounted under cab & bed. MY23+ requires RF bed	X			
<b>F450 Pickup 2" Lift Kit</b>																		
Front F450 Pickup (4x4 or 4x2)	2020-2022	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS3PW-L2 6000	Front suspension with Dual Springs (Requires DS103FS2P-L2DS/-L2SS rear suspension) <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X			
													FS60FS3PW-L2E <sup>1</sup> 6000		X			
	2023-Current	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS4PW-L2 6000		X			
													FS60FS4PW-L2E <sup>1</sup> 6000		X			
Rear F450 DRW Pickup	2020-Current	10300	DRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-L2DS 10300	Removes spare tire. Volumes & power module mounted behind rear axle. <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X			
													DS103FS2P-L2DSE <sup>1</sup> 10300		X			
	2020-Current	10300	DRW Only	Any	Any	56	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-L2SS 10300	Long bed required. Volumes & power module mounted under cab & bed. MY23+ requires RF bed side step to be replaced (included in kit). <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X			

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

														Application					
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle	
<sup>1</sup> International export models have 0 psi precharge accumulators																			
<b>F450 Pickup 4" Lift Kit</b>																			
Front F450 Pickup (4x4 or 4x2)	2020-2022	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	No	FS60FS3PW-L4 6000	Front suspension with Dual Springs (Requires DS103FS2P-L4DS rear suspension) <b>Requires dual steering stabilizer kit<sup>2</sup></b>	X				
													FS60FS3PW-L4E <sup>1</sup>		X				
	2023-Current	5990	n/a	Any	Any	Any	n/a	Any	n/a	n/a	n/a	n/a	No	FS60FS4PW-L4 6000	Note: Installation of LiquidSpring suspension will disable onboard scale & smart hitch functionality. OEM hitch only.	X			
														FS60FS4PW-L4E <sup>1</sup> 6000		X			
Rear F450 DRW Pickup	2020-Current	10300	DRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-L4DS 10300	Removes spare tire. Volumes & power module mounted behind rear axle <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X				
	2020-Current	10300	DRW Only	Any	Any	Any	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-L4DSE <sup>1</sup> 10300	<b>Empty Accumulator.</b> Removes spare tire. Volumes & power module mounted behind rear axle. <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X				
	2020-Current	10300	DRW Only	Any	Any	56	n/a	Any	Standard	n/a	n/a	No	DS103FS2P-L4SS 10300	Long bed required. Volumes & power module mounted under cab & bed. MY23+ requires RF bed side step to be replaced (included in kit). <b>Note: Installation of LiquidSpring suspension will disable onboard scale &amp; smart hitch functionality. OEM hitch only.</b>	X				

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

															Application			
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
<sup>1</sup> International export models have 0 psi precharge accumulators																		
<sup>2</sup> Recommended dual steering stabilizer kit: "RealTruck Superlift Dual Steering Stabilizer Kit with Fox 2.0 Series Shocks" (p/n: 92766)																		
<b>F450 Cab Chassis Stock Height</b>																		
<b>FRONT F450 Cab Chassis (4x4 or 4x2)</b>	2017-Current	7000	n/a	Reg. 169 Reg. 193 Super 205 Crew 205	169 193 205 205	84 108 120 84	n/a	Any	n/a	n/a	n/a	No	FS70F 7000	Front Suspension (requires DS112FS4-A or DS147FS4-A/-AF/-ANY Rear) <b>Note: Pre-4X conversion kit p/n: 11547</b>	X	X	X	X
	2017-Current	7000	n/a	Reg. 169 Reg. 193 Super 205 Crew 205	169 193 205 205	84 108 120 84	n/a	Any	n/a	n/a	n/a	No	FS70FF 7000	Front Suspension (requires DS112FS4-A or DS147FS4-A/-AF/-ANY Rear) <b>Note: Pre-4X conversion kit p/n: 11547</b>		X		
<b>REAR F450 Cab Chassis (4x4 or 4x2)</b>	2017-Current	12880	n/a	Reg. 169	169	84	n/a	Gas Diesel	Any Rear	n/a	n/a	Yes	DS112FS4-A 11200	<b>Note: 2017 models require steering sensor kit p/n: 11520</b> Power module: Between frameraills under back of cab. Volumes: Along frame behind cab	X			
				Reg. 193	193	108	n/a	Gas Diesel	Any Rear									
				Reg. 205	205	120	n/a	Any	Any									
				Reg. 169	169	84	n/a	Gas Diesel	Any Rear									
				Reg. 193	193	108	n/a	Gas Diesel	Any Rear				DS147FS4-A 14706	<b>Note: 2017 models require steering sensor kit p/n: 11520</b> Power module: Between frameraills under back of cab. Volumes: Along frame behind cab	X			
				Reg. 205	205	120	n/a	Any	Any									
				Super 192	192	84	n/a	Gas Diesel	Any Rear									
				Crew 205	205	84	n/a	Gas Diesel	Any Rear									
Reg. 145 Reg. 169 Reg. 193	145 169 193	60+	n/a	Diesel	Rear	n/a	n/a	Yes	DS147FS4-DS60D 14706	<b>Note: 2017 models require steering sensor kit p/n: 11520</b> Power Module: Between frameraills under back of cab	X							
Reg. 145 Reg. 169 Reg. 193	145 169 193	60+	n/a	Gas	Rear											DS147FS4-DS60G 14706	<b>Note: 2017 models require steering sensor kit p/n: 11520</b> Power Module: Between frameraills under back of cab	X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application			
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle	
	2011-2016	12000	n/a	Reg. Reg.	165 189	84 108	n/a	Any	Mid*, Rear	n/a	n/a	Yes	DS137FS2 13660	* Mid ship fuel tank may require relocation of OEM DEF tank on 84" and 108" CA vehicles.	X	X		
	2008-2010	12000	n/a	Reg. Reg. Super Crew	165 189 201 186 200	84 108 84 84 84	n/a	Any	Mid*, Rear	n/a	n/a	Yes	DS137FS2-10 13660	* Mid ship fuel tank may require relocation of OEM DEF tank on 84" and 108" CA vehicles.	X	X		
<b>F550 Cab Chassis Stock Height</b>																		
FRONT F550 Cab Chassis (4x4 or 4x2)	2017-Current	7000	n/a	Reg. Reg. Super Crew	169 193 205 192 205	84+	n/a	Any	n/a	n/a	n/a	No	FS70F 7000	Front Suspension (requires DS112FS4-A or DS147FS4-A/-AF/-ANY or DS155FS4 Rear) <b>Note: Pre-4X conversion kit p/n: 11547</b>	X	X	X	X
	2017-Current	7000	n/a	Reg. Reg. Super Crew	169 193 205 192 205	84+	n/a	Any	n/a	n/a	n/a	No	FS70FF 7000	Front Suspension (requires DS112FS4-A or DS147FS4-A/-AF/-ANY or DS155FS4 Rear) <b>Note: Pre-4X conversion kit p/n: 11547</b>		X		
	2017-Current	7500	n/a	Reg. Reg. Super Crew	169 193 205 192 205	84+	n/a	Any	n/a	n/a	n/a	No	FS75F 7500	Front Suspension (requires DS112FS4-A or DS147FS4-A/-AF/-ANY or DS155FS4 Rear) <b>Note: Pre-4X conversion kit p/n: 11547</b>	X	X	X	X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
	2017-Current	7500	n/a	Reg. 169 Reg. 193 Super 205 Crew 192 205	169 193 205 192 205	84+	n/a	Any	n/a	n/a	n/a	No	FS75FTE 7500	Front Suspension (requires DS147FS4-L2SSTE/-L4SSTE or DS155FS4-L2SSTE/-L4SSTE Rear) <b>Note: Pre-4X conversion kit p/n: 11547</b> System is equipped with Tru-Earth Leveling™.			X
	2017-Current	7500	n/a	Reg. 169 Reg. 193 Super 205 Crew 192 205	169 193 205 192 205	84+	n/a	Any	n/a	n/a	n/a	No	FS75FS2-MTE 7500	Front Suspension (requires DS155FS4-L2MTE/-L4MTE, DS155FS4-L2RTE/-L4RTE, or DS155FS4-L2DRTE/L4DRTE Rear) <b>Note: Pre-4X conversion kit p/n: 11547</b> System is equipped with Tru-Earth Leveling™.			X
REAR F550 Cab Chassis 17500 GVW (4x4 or 4x2)	2017-Current	13660	n/a	Reg.	169	84	n/a	Gas Diesel	Any Rear	n/a	n/a	Yes	DS112FS4-A 11200	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumes: Along frame behind cab	X	X	
				Reg.	193	108	n/a	Gas Diesel	Any Rear								
				Reg.	205	120	n/a	Any	Any								
				Reg.	169	84	n/a	Gas Diesel	Any Rear				DS147FS4-A 14706	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumes: Along frame behind cab			
				Reg.	193	108	n/a	Gas Diesel	Any Rear								
				Reg.	205	120	n/a	Any	Any								
				Super	192	84	n/a	Gas Diesel	Any Rear				DS147FS4-AF 14706	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Behind rear fuel tank Volumes: Along frame behind cab			
				Crew	205	84	n/a	Gas Diesel	Any Rear								
				Reg.	169	84	n/a										
				Reg.	193	108	n/a						DS147FS4-ANY 14706	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Behind rear fuel tank Volumes: Between frame rails, behind front hanger			
				Reg.	205	120	n/a	Diesel	Rear								
				Super	192	84	n/a										
				Crew	205	84	n/a						DS147FS4-DS60D 14706	Note: 2017 models require steering sensor kit p/n: 11520 Power Module: Between framersails under back of cab			
				Reg.	145	60+	n/a	Diesel	Rear								
Reg.	169	84	n/a														
Reg.	193	108	n/a			DS147FS4-DS60G 14706	Note: 2017 models require steering sensor kit p/n: 11520 Power Module: Between framersails under back of cab										
Super	192	84	n/a	Gas	Rear												
Crew	205	84	n/a														
Reg.	145	60+	n/a														
Reg.	169	84	n/a														
Reg.	193	108	n/a														
Super	192	84	n/a														
Crew	205	84	n/a														

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application																
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle														
	2011-2016	13660	n/a	Reg. 165, 189, 201 Reg. 186, 200 Super Crew	165, 189, 201	84, 108, 120, 84, 84	n/a	Any	Mid*, Rear	n/a	n/a	Yes	DS137FS2 13660	* Mid ship fuel tank may require relocation of OEM DEF tank on 84" and 108" CA vehicles.	X	X	X	X													
	2008-2010	13660	n/a	Reg. 165, 189, 201 Reg. 186, 200 Super Crew	165, 189, 201	84, 108, 120, 84, 84	n/a	Any	Mid*, Rear	n/a	n/a	Yes	DS137FS2-10 13660	* Mid ship fuel tank may require relocation of OEM DEF tank on 84" and 108" CA vehicles.	X	X	X														
REAR F550 Cab Chassis 19500 GVW (4x4 or 4x2)	2017-Current	14706	n/a	Reg. 169 Reg. 193 Reg. 205 Reg. 169 Reg. 193 Reg. 205 Super 192 Crew 205	169 193 205 169 193 205 192 205	84 108 120 84 108 120 84 84	n/a	Gas Diesel	Any Rear	n/a	n/a	n/a	Yes	DS112FS4-A 11200	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumes: Along frame behind cab	X	X	X	X												
																				DS147FS4-A 14706	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumes: Along frame behind cab										
																						DS147FS4-AF 14706	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Behind rear fuel tank Volumes: Along frame behind cab								
																								DS147FS4-ANY 14706	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Behind rear fuel tank Volumes: Between frame rails, behind front hanger						
																										DS147FS4-ANYBA 14706	Note: 2017 models require steering sensor kit p/n: 11520 Kit				
																												DS155FS4 15500	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumes: Along frame behind cab		
																														DS155FS4-F 15500	Note: 2017 models require steering sensor kit p/n: 11520 Power module: Behind rear fuel tank Volumes: Along frame behind cab

### LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
				Reg. Super Crew	205-257	n/a	n/a	Any	Mid, Rear	n/a	n/a	Yes	DS147FS4-B 14706	<b>Note: 2017 models require steering sensor kit p/n: 11520</b> Kit created to accommodate bus chassis that have a			X
				Reg. Reg. Reg.	145 169 193									<b>Note: 2017 models require steering sensor kit p/n: 11520</b>			

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
				Reg. Super Crew	155 168 180 205	60+	n/a	Diesel	Rear	n/a	n/a	Yes	DS147FS4-DS60D 14706	Power Module: Between framerails under back of cab Volumes: Between framerails, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
REAR F550 Cab Chassis 19500 GVW (4x4 or 4x2)	2017-Current	14706	n/a	Reg. Reg. Reg. Super Super Crew Crew	145 169 193 205 168 192 180 205	60+	n/a	Gas	Rear	n/a	n/a	Yes	DS147FS4-DS60G 14706	<b>Note: 2017 models require steering sensor kit p/n: 11520</b> Power Module: Between framerails under back of cab Volumes: Between framerails, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
				Crew	180	60	n/a	Gas	Rear	n/a	n/a	Yes	DS147FS4-P 14706	<b>Note: 2017 models require steering sensor kit p/n: 11520</b> Patriot3 specific kit. Power Module: Between framerails under back of cab Volumes: Between framerails, behind front hanger	X		

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application			
															Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
	2011-2016	14706	n/a	Reg. Reg.	165, 189	84, 108	n/a	Any	Mid*, Rear	n/a	n/a	Yes	DS147FS2 14704	* Mid ship fuel tank may require relocation of OEM DEF tank on 84" and 108" CA vehicles.	X	X	X	X
	2011-2016	14706	n/a	Reg.	189	108	n/a	Any	Rear	n/a	n/a	Yes	DS147FS2-NY 14704	Kit created to work with FDNY ambulance (with Telma Retarder). Volumes are double stacked inside frame on LH side. PM located behind rear fuel tank.		X		
<b>F600 Cab Chassis Stock Height</b>																		
FRONT F600 Cab Chassis (4x4 or 4x2)	2017-Current	7500	n/a	Reg. Reg. Super Crew	169, 193, 205, 192, 205	84+	n/a	Any	n/a	n/a	n/a	No	FS70F 7000	<b>Note: Front suspension derates from 7500 to 7000 lbs</b> Requires Rear DS155FS4 kit	X		X	X
	2017-Current	7500	n/a	Reg. Reg. Super Crew	169, 193, 205, 192, 205	84+	n/a	Any	n/a	n/a	n/a	No	FS70FF 7000	<b>Note: Front suspension derates from 7500 to 7000 lbs</b> Requires Rear DS155FS4-F kit	X		X	X
	2017-Current	7500	n/a	Reg. Reg. Super Crew	169, 193, 205, 192, 205	84+	n/a	Any	n/a	n/a	n/a	No	FS75F 7500	Requires Rear DS155FS4-F kit	X		X	X
	2017-Current	7500	n/a	Reg. Reg.	169, 193	84+	n/a	Any	n/a	n/a	n/a	No	FS75FTE 7500	Front Suspension (requires DS147/FS4-LZSSTE/-L4SSTE)				X
	2017-Current	7500	n/a	Reg. Reg.	169, 193	84+	n/a	Any	n/a	n/a	n/a	No	FS75FS2-MTE 7500	Front Suspension (requires DS133FS4-LZMITE/-L4MITE, DS155FS4-L2RTE/-L4RTE, or DS155FS4-L2DRTE/-L4DRTE)				X
REAR F600 Cab Chassis 22000 GVW (4x4 or 4x2)	2017-Current	15500	n/a	Reg.	169	84	n/a	Gas	Any	n/a	n/a	Yes	DS155FS4 15500	<b>Note: 2017 models require steering sensor kit p/n: 11520</b> Power module: Inside frame behind cab Volumes: Along frame behind cab	X		X	X
								Diesel	Rear									
				Reg.	193	108	n/a	Diesel	Rear									
								Reg.	205									
				Reg. Super	205-257	n/a	n/a	Any	Mid, Rear									
				Super	192	84	n/a	Gas	Any									
								Diesel	Rear									
														<b>Note: 2017 models require steering sensor kit p/n: 11520</b>			X	
														<b>Note: 2017 models require steering sensor kit p/n: 11520</b>				

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application				
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle		
				Crew	205	84	n/a	Gas Diesel	Any Rear				DS155FS4-F 15500	<b>11520</b> Power module: Behind rear fuel tank Volumes: Along frame behind cab			X	X	
<b>F450/550/600 Cab Chassis 2" Lift Kit</b>																			
<b>FRONT F450/550 Cab Chassis (4x4 or 4x2)</b>	2017-2022	7000	n/a	Reg. Reg.	169 193	60+	n/a	Any	Any	n/a	n/a	n/a	FS70FS3-L2 7000	Requires Rear DS100FS4-L2DSD/-L2DSG or DS147FS4-L2DSD/-L2DSG/-L2SS/-L4DSD/-L4DSG/-L4SS or DS155FS4-L2DSD/-L2DSG/-L2SS/-L4DSD/-L4DSG/-L4SS	X				
				Reg. Super Crew	205 192 205								FS70FS3-L2TE 7000	Requires Rear DS147FS4-L2SSTE/-L4SSTE or DS155FS4-L2SSTE/-L4SSTE. System is equipped with Tru-Earth Leveling™.	X			X	
	2017-2022	7000	n/a	Reg. Reg.	169 193	60+	n/a	Any	Any	n/a	n/a	n/a	FS70FS3-L2M 7000	Requires Rear DS155FS4-L4M	X				X
				Reg. Super Crew	205 192 205								FS70FS3-L2MTE 7000	Requires Rear DS155FS4-L2DRTE/-L2MTE/-L2RTE/-L4DRTE/-L4MTE/-L4RTE System is equipped with Tru-Earth Leveling™.	X			X	
	2023+	7000	n/a	Reg. Reg.	169 193	60+	n/a	Any	Any	n/a	n/a	n/a	FS70FS4-L2 7000	Requires Rear DS100FS4-L2DSD/-L2DSG or DS147FS4-L2DSD/-L2DSG/-L2SS/-L4DSD/-L4DSG/-L4SS or DS155FS4-L2DSD/-L2DSG/-L2SS/-L4DSD/-L4DSG/-L4SS	X				
				Reg. Super Crew	205 192 205								FS70FS4-L2TE 7000	Requires Rear DS147FS4-L2SSTE/-L4SSTE or DS155FS4-L2SSTE/-L4SSTE. System is equipped with Tru-Earth Leveling™.	X			X	

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application			
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle	
	2023+	7000	n/a	Reg. Reg. Super Crew	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS70FS4-L2M 7000	Requires Rear DS155FS4-L4M	X		X	
													FS70FS4-L2MTE 7000	Requires Rear DS155FS4-L2DRTE/-L2MTE/-L2RTE/-L4DRTE/-L4MTE/-L4RTE System is equipped with Tru-Earth Leveling™.	X		X	
FRONT F550/600 Cab Chassis (4x4 or 4x2)	2017-2022	7500	n/a	Reg. Reg. Super Crew	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS75FS3-L2 7500	Requires Rear DS100FS4-L2DSD/-L2DSG or DS147FS4-L2DSD/-L2DSG/-L2SS/-L4DSD/-L4DSG/-L4SS or DS155FS4-L2DSD/-L2DSG/-L4SS/-L4DSD/-L4DSG/-L4SS	X			
													FS75FS3-L2TE 7500	Requires Rear DS147FS4-L2SSTE/-L4SSTE or DS155FS4-L2SSTE/-L4SSTE. System is equipped with Tru-Earth Leveling™.	X		X	
	2017-2022	7500	n/a	Reg. Reg. Super Crew	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS75FS3-L2M 7500	Requires Rear DS155FS4-L4M	X		X	
													FS75FS3-L2MTE 7500	Requires Rear DS155FS4-L2DRTE/-L2MTE/-L2RTE/-L4DRTE/-L4MTE/-L4RTE System is equipped with Tru-Earth Leveling™.	X		X	
	2023+	7500	n/a	Reg. Reg. Super Crew	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	n/a	FS75FS4-L2 7500	Requires Rear DS100FS4-L2DSD/-L2DSG or DS147FS4-L2DSD/-L2DSG/-L2SS/-L4DSD/-L4DSG/-L4SS or DS155FS4-L2DSD/-L2DSG/-L4SS/-L4DSD/-L4DSG/-L4SS	X		
														FS75FS4-L2TE 7500	Requires Rear DS147FS4-L2SSTE/-L4SSTE or DS155FS4-L2SSTE/-L4SSTE. System is equipped with Tru-Earth Leveling™.	X		X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
	2023+	7500	n/a	Reg. Reg. Super Crew	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS75FS4-L2M 7500	Requires Rear DS155FS4-L4M	X		X
													FS75FS4-L2MTE 7500	Requires Rear DS155FS4-L2DRTE/-L2MTE/-L2RTE/-L4DRTE/-L4MTE/-L4RTE System is equipped with Tru-Earth Leveling™.	X		X
REAR F450/550/600 Cab Chassis (4x4 or 4x2)	2017+	10000	n/a	Reg. Reg. Super Crew	145 169 193 205 168 192 180 205	60+	n/a	Diesel	Rear	n/a	n/a	Yes	DS100FS4-L2DSD 10000	<b>2017 models require steering sensor kit p/n: 11520</b> Power Module: Between framereils under back of cab. Volumes: Between framereils, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
								Gas					DS100FS4-L2DSG 10000	Power Module: Between framereils under back of cab. Volumes: Between framereils, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
	2017+	14706	n/a	Reg. Reg. Super Crew	145 169 193 205 168 192 180 205	60+	n/a	Diesel	Rear	n/a	n/a	Yes	DS147FS4-L2DSD 14706	<b>2017 models require steering sensor kit p/n: 11520</b> Power Module: Between framereils under back of cab. Volumes: Between framereils, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
								Gas					DS147FS4-L2DSG 14706	Power Module: Between framereils under back of cab. Volumes: Between framereils, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
	2017+	14706	n/a	Reg. Reg. Super Crew	169 193 205 192 205	84+	n/a	Any	Any	n/a	n/a	Yes	DS147FS4-L2SS 14706	<b>2017 models require steering sensor kit p/n: 11520</b> Power module: Inside frame behind cab Relocated Volumes: Along frame behind cab DEF tank will require kit 12315	X		
													DS147FS4-L2SSTE 14706	<b>2017 models require steering sensor kit p/n: 11520</b> Power module: Inside frame behind cab Relocated Volumes: Along frame behind cab DEF tank will require kit 12315 System is equipped with Tru-Earth Leveling™.	X		X
2017+	15500	n/a	Reg. Reg. Super Crew	145 169 193 205	60+	N/A	Diesel	Rear	n/a	n/a	Yes	DS155FS4-L2DSD 15500	<b>2017 models require steering sensor kit p/n: 11520</b> Power Module: Between framereils under back of cab. Volumes: Between framereils, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X			

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
	2017+	15500	n/a	Super Super Crew Crew	168 192 180 205	80+	n/a	Gas	Rear	n/a	n/a	Yes	DS155FS4-L2DSG 15500	2017 models require steering sensor kit p/n: 11520 Power Module: Between framrails under back of cab. Volumes: Between framrails, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
	2017+	15500	n/a	Reg. Reg. Super Crew	169 193 205 192 205	84+	n/a	Any	Any	n/a	n/a	Yes	DS155FS4-L2DRTE 15500	2017 models require steering sensor kit p/n: 11520 Power module: On crossmember behind rear fuel tank Volumes: Double stacked behind rear axle. Relocated DEF tank will require kit 12315 System is equipped with Tru-Earth Leveling™.	X		X
REAR F450/550/600 Cab Chassis	2017+	15500	n/a	Reg. Reg. Super Crew	169 193 205 192 205	84+	n/a	Any	Any	n/a	n/a	Yes	DS155FS4-L2SS 15500	2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumes: Along frame behind cab Relocated DEF tank will require kit 12315	X		
													DS155FS4-L2SSTE 15500	2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumes: Along frame behind cab Relocated DEF tank will require kit 12315 System is equipped with Tru-Earth Leveling™.	X		X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
(4x4 or 4x2)	2017+	15500	n/a	Reg. 169 Reg. 193 Reg. 205	169 193 205	84+	n/a	Any	Any	n/a	n/a	Yes	DS155FS4-L2MTE 15500	2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumer: Double stacked behind rear axle	X		X
	2017+	15500	n/a	Reg. 169 Reg. 193 Reg. 205 Super 192	169 193 205 192	84+	n/a	Any	Any	n/a	n/a	Yes	DS155FS4-L2RTE 15500	2017 models require steering sensor kit p/n: 11520 Power module: On crossmember behind rear fuel tank. Volumer: Single stacked on outside of frame. Relocated DEF tank will require kit 12315	X		X
<b>F450/550/600 Cab Chassis 4" Lift Kit</b>																	
FRONT F450/550 Cab Chassis (4x4 or 4x2)	2018-2022	7000	n/a	Reg. 169 Reg. 193 Reg. 205 Super Crew	169 193 205 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS70FS3-L4 7000	Requires Rear DS147FS4-L4DSD/-L4SS or DS155FS4-L4DSD/-L4SS <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X		
													FS70FS3-L4TE 7000	Requires Rear DS147FS4-L4DSDTE/-L4SSTE or DS155FS4-L4DSDTE/-L4SSTE System is equipped with Tru-Earth Leveling™. <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X		
	2018-2022	7000	n/a	Reg. 169 Reg. 193 Reg. 205 Super Crew	169 193 205 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS70FS3-L4M 7000	Requires Rear DS155FS4-L4M <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X		X
													FS70FS3-L4MTE 7000	Requires Rear DS155FS4-L4DRTE/-L4MTE/-L4RTE System is equipped with Tru-Earth Leveling™. <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X		X
	2023+	7000	n/a	Reg. 169 Reg. 193 Reg. 205 Super Crew	169 193 205 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS70FS4-L4 7000	Requires Rear DS147FS4-L4DSD/-L4SS or DS155FS4-L4DSD/-L4SS <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X		
													FS70FS4-L4TE 7000	Requires Rear DS147FS4-L4DSDTE/-L4SSTE or DS155FS4-L4DSDTE/-L4SSTE System is equipped with Tru-Earth Leveling™. <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X		
				Reg. 169 Reg. 193	169 193								FS70FS4-L4M	Requires Rear DS155FS4-L4M	X		X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

														Application				
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
	2023+	7000	n/a	Reg. Super Crew	193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS70FS4-L4MTE 7000	Requires Rear DS155FS4-L4DRTE/-L4MTE/-L4RTE System is equipped with Tru-Earth Leveling™. <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X			X
<sup>1</sup> Recommended dual steering stabilizer kit: "RealTruck Superlift Dual Steering Stabilizer Kit with Fox 2.0 Series Shocks" (p/n: 92766)																		
FRONT F550/600 Cab Chassis (4x4 or 4x2)	2018-2022	7500	n/a	Reg. Super Crew	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS75FS3-L4 7500	Requires Rear DS147FS4-L4DSD/-L4SS or DS155FS4-L4DSD/-L4SS <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X			
													FS75FS3-L4TE 7500	Requires Rear DS147FS4-L4DSDTE/-L4SSTE or DS155FS4-L4DSDTE/-L4SSTE System is equipped with Tru-Earth Leveling™. <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X			
	2018-2022	7500	n/a	Reg. Super Crew	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS75FS3-L4M 7500	Requires Rear DS155FS4-L4M <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X			X
													FS75FS3-L4MTE 7500	Requires Rear DS155FS4-L4DRTE/-L4MTE/-L4RTE System is equipped with Tru-Earth Leveling™. <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X			X
	2023+	7500	n/a	Reg. Super Crew	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS75FS4-L4 7500	Requires Rear DS147FS4-L4DSD/-L4SS or DS155FS4-L4DSD/-L4SS <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X			
													FS75FS4-L4TE 7500	Requires Rear DS147FS4-L4DSDTE/-L4SSTE or DS155FS4-L4DSDTE/-L4SSTE System is equipped with Tru-Earth Leveling™. <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X			
		7500	n/a	Reg. Super Crew	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS75FS4-L4M 7500	Requires Rear DS155FS4-L4M <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X			X
													FS75FS4-L4MTE	Requires Rear DS155FS4-L4DRTE/-L4MTE/-L4RTE	X			X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
	2023+	9500	n/a	Reg. 169 Reg. 193 Reg. 205 Super 192 Crew 205	169 193 205 192 205	60+	n/a	Any	Any	n/a	n/a	n/a	FS95FS4-L4AV 9500	Special unit for INKAS; Requires Rear DS155FS4-L4AV. <b>Requires dual steering stabilizer kit<sup>1</sup></b>	X		
<sup>1</sup> Recommended dual steering stabilizer kit: "RealTruck Superlift Dual Steering Stabilizer Kit with Fox 2.0 Series Shocks" (p/n: 92766)																	
Rear F450/550/600 Cab Chassis (4x4 or 4x2)	2017+	10000	n/a	Reg. 145 Reg. 169 Reg. 193 Reg. 205 Super 168	145 169 193 205 168	60+	n/a	Diesel	Any	n/a	n/a	Yes	DS100FS4-L4DSD 10000	<b>2017 models require steering sensor kit p/n: 11520</b> Power Module: Between framerrails under back of cab. Volumes: Between framerrails, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
	2017+	14706	n/a	Reg. 145 Reg. 169 Reg. 193 Reg. 205 Super 168 Super 192 Crew 180 Crew 205	145 169 193 205 168 192 180 205	60+	n/a	Diesel	Any	n/a	n/a	Yes	DS147FS4-L4DSD 14700	<b>2017 models require steering sensor kit p/n: 11520</b> Power Module: Between framerrails under back of cab. Volumes: Between framerrails, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
								Gas					DS147FS4-L4DSG 14700	<b>2017 models require steering sensor kit p/n: 11520</b> Power Module: Between framerrails under back of cab. Volumes: Between framerrails, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-267R4	X		
	2017+	14706	N/A	Reg. 169 Reg. 193 Reg. 205 Super 192 Crew 205	169 193 205 192 205	84+	n/a	Any	Any	Any	n/a	n/a	Yes	DS147FS4-L4SS 14706	<b>2017 models require steering sensor kit p/n: 11520</b> Power module: Inside frame behind cab Volumes: Along frame behind cab Relocated DEF tank will require kit 12315	X	
DS147FS4-L4SSTE 14706														<b>2017 models require steering sensor kit p/n: 11520</b> Power module: Inside frame behind cab Volumes: Along frame behind cab Relocated DEF tank will require kit 12315 System is equipped with Tru-Earth Leveling™.	X		X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
Rear F450/550/600 Cab Chassis (4x2) (4x4)	2017+	15500	N/A	Reg. 145 Reg. 169 Reg. 193 Super 205 Super 168 Super 192 Crew 180 Crew 205	60+	n/a	Diesel	Any	n/a	n/a	Yes	DS155FS4-L4AV 15500	Special unit for INKAS; 2017 models require steering sensor kit p/n: 11520	X			
												DS155FS4-L4DSD 15500	2017 models require steering sensor kit p/n: 11520 Power Module: Between framrails under back of cab. Volumes: Between framrails, behind front hanger Ford DEF relocation kit is required. Refer to SVE Bulletin Q-	X			
	2017+	15500	N/A	Reg. 169 Reg. 193 Reg. 205 Super 192 Crew 205	84+	n/a	Any	Rear	n/a	n/a	Yes	DS155FS4-L4DRTE 15500	2017 models require steering sensor kit p/n: 11520 Power module: On crossmember behind rear fuel tank Volumes: Double stacked behind rear axle. Relocated DEF tank will require kit 12315 System is equipped with Tru-Earth Leveling™.	X		X	
												DS155FS4-L4SS 15500	2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumes: Along frame behind cab Relocated DEF tank will require kit 12315	X			
					Reg. 169 Reg. 193 Reg. 205 Super 192 Crew 205	84+	n/a	Any	Any	n/a	Yes	DS155FS4-L4SSTE 15500	2017 models require steering sensor kit p/n: 11520 Power module: Inside frame behind cab Volumes: Along frame behind cab Relocated DEF tank will require kit 12315 System is equipped with Tru-Earth Leveling™.	X		X	
	Rear F450/550/600 Cab Chassis (4x4 or 4x2)	2017+	15500	N/A	Reg. 169 Reg. 193 Reg. 205 Super 192 Crew 205	84+	n/a	Any	Rear	n/a	n/a	Yes	DS155FS4-L4M 15500	2017 models require steering sensor kit p/n: 11520 Power module: Outboard of passenger side frame in front of rear axle Volumes: Double stacked behind rear axle Relocated DEF tank will require kit 12315	X		X
													DS155FS4-L4MTE 15500	2017 models require steering sensor kit p/n: 11520 Power module: Outboard of passenger side frame in front of rear axle Volumes: Double stacked behind rear axle. Relocated DEF tank will require kit 12315 System is equipped with Tru-Earth Leveling™.	X		X
DS155FS4-L4RTE 15500													2017 models require steering sensor kit p/n: 11520 Power module: Outboard behind fuel tank. Volumes: Single Stacked on outside of frame. Relocated DEF tank will require kit 12315 System is equipped with Tru-Earth Leveling™.	X		X	
<b>F650</b>																	
F650	2016-Current	17500-19000 (13500)	Dana S140	Any	158+	84+	10.126" Straight (534)	Any	Forward Only	Hydraulic Only	19000-21000 Leaf Springs	TBD	DS135F650SR-SHR 13500	Volumes rear, PM rear, Lower ride height (designed for ambulance w/ 19.5" tires)		X	
	2016-Current	17500-19000 (13500)	Dana S140	Any	158+	84+	10.126" Straight (534)	Any	Any	Hydraulic Only	19000-21000 Leaf Springs	TBD	DS135F650SR-SHF 13500	Volumes forward, PM forward LH inboard frame			X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
<b>REAR F650 Straight Rail Frame</b>	2016-Current	17500-19000 (15500)	Dana S140	Any	158+	84+	10.126" Straight (534)	Any	Any	Hydraulic Only	19000-21000 Leaf Springs	TBD	DS155F650SR-SHB 15500	Volumes forward, PM forward LH inboard frame			X
	2016-Current	17500-19000 (19000)	Dana S140	Any	158+	84+	10.126" Straight (534)	Any	Any	Hydraulic Only	19000-21000 Leaf Springs	TBD	DS190F650SR-SHB 19000	Volumes forward, PM forward LH inboard frame			X
<b>F53</b>																	
<b>FRONT F53 16K GVW</b>	2009-2019	7000	n/a	n/a	158 178 190	n/a	n/a	n/a	n/a	n/a	Steel Leaf 6500	No	FS70F53S2TE 7000 (FS70F53S2C)	Front Suspension (requires DS120F53S2TE Rear kit) 158" WB requires 11468 to mount PM aft of fuel tank FS70F53S2C includes FS70F53S2TE and conversion kits for existing vehicles with DS120F53 installed. System is equipped with Tru-Earth Leveling.			X
													FS70F53S2-DSTE 7000	Front Suspension (requires DS120F53S2-DSTE Rear) Double Stack Front Volumes in-board at front. PM aft of fuel tank. System is equipped with Tru-Earth Leveling.			X
<b>FRONT F53 18K GVW</b>	2009-2019	7000	n/a	n/a	178 190 208	n/a	n/a	n/a	n/a	n/a	Steel Leaf 7000	No	FS70F53S2TE 7000 (FS70F53S2C)	Front Suspension (requires DS120F53S2TE Rear kit) FS70F53S2C includes FS70F53S2TE and conversion kits for existing vehicles with DS120F53 installed. System is equipped with Tru-Earth Leveling.			X
													FS70F53S2-DSTE 7000	Front Suspension (requires DS120F53S2-DSTE Rear) Double Stacked Front Volumes in-board at front. PM aft of fuel tank. System is equipped with Tru-Earth Leveling.			X
<b>FRONT F53 20.5K GVW</b>	2009-2019	7000	n/a	n/a	208 228	n/a	n/a	n/a	n/a	n/a	Steel Leaf 7000	No	FS80F53S2TE 8000 (FS80F53S2C)	Front Suspension (requires DS150F53S2TE or DS150F53S2-DSTE Rear kit). FS80F53S2C includes FS80F53S2TE and conversion kits for existing vehicles with DS150F53 installed. System is equipped with Tru-Earth Leveling.			X
													FS80F53S2-DSTE 8000	Front Suspension (requires DS150F53S2-DSTE or DS150F53S2TE Rear kit). Double Stack Front Volumes in-board at front. System is equipped with Tru-Earth Leveling.			X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
FRONT F53 22K GVW	2009-2019	8000	n/a	n/a	208 228 242	n/a	n/a	n/a	n/a	n/a	Steel Leaf 8000	No	FS80F53S2TE 8000 (FS80F53S2C)	Front Suspension (requires DS150F53S2TE or DS150F53S2-DSTE Rear kit). FS80F53S2C includes FS80F53S2TE and conversion kits for existing vehicles with DS150F53 installed. System is equipped with Tru-Earth Leveling.			X
													FS80F53S2-DSTE 8000	Front Suspension (requires DS150F53S2-DSTE or DS150F53S2TE Rear kit). Double Stack Front Volumes in-board at front. System is equipped with Tru-Earth Leveling.			X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
FRONT F53 24K GVW	2009-2019	9000	n/a	n/a	228 242 252	n/a	n/a	n/a	n/a	n/a	Steel Leaf 9000	No	FS90F53S2TE 9000 (FS90F2C)	Front Suspension (requires DS175F53S2TE or DS175F53S2-DSTE Rear kit). Front Sway Bar Kit- P/N: 12125 FS90F2C includes FS90F53S2TE and conversion kits for existing vehicles with DS175F53 installed. System is equipped with Tru-Earth Leveling.			X
													FS90F53S2-DSTE 9000	Front Suspension (requires DS175F53S2-DSTE or DS175F53S2TE Rear kit). Front Sway Bar Kit- P/N: 12125 Double Stack Front Volumes in-board at front. System is equipped with Tru-Earth Leveling.			X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
FRONT F53 26K GVW	2009-2019	9000	n/a	n/a	228	n/a	n/a	n/a	n/a	n/a	Steel Leaf 9000	No	FS90F53S2TE 9000 (FS90F2C)	Front Suspension (requires DS175F53S2TE or DS175F53S2-DSTE Rear kit). Front Sway Bar Kit- P/N: 12125			X
					242								FS90F53S2-DSTE 9000	Front Suspension (requires DS175F53S2-DSTE or DS175F53S2TE Rear kit). Front Sway Bar Kit- P/N: 12125 Double Stack Front Volumes in-board at front. System is equipped with Tru-Earth Leveling™.			X
FRONT F53 16K GVW	2020+	7000	n/a	n/a	158	n/a	n/a	n/a	n/a	n/a	Steel Leaf 6500	No	FS70F53S3TE 7000	Front Suspension (requires DS120F53S3TE Rear kit). 158" WB requires 11468 to mount PM aft of fuel tank System is equipped with Tru-Earth Leveling™.			X
					178								FS70F53S3-DSTE 7000	Front Suspension (requires DS120F53S3-DSTE Rear). Double Stack Front Volumes in-board at front. PM aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
FRONT F53 18K GVW	2020+	7000	n/a	n/a	190	n/a	n/a	n/a	n/a	n/a	Steel Leaf 7000	No	FS70F53S3TE 7000	Front Suspension (requires DS120F53S3TE Rear kit). System is equipped with Tru-Earth Leveling™.			X
					208								FS70F53S3-DSTE 7000	Front Suspension (requires DS120F53S3-DSTE Rear). Double Stack Front Volumes in-board at front. PM aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
FRONT F53 20.5K GVW	2020+	7000	n/a	n/a	208	n/a	n/a	n/a	n/a	n/a	Steel Leaf 7000	No	FS80F53S3TE 8000	Front Suspension (requires DS150F53S3TE or DS150F53S3-DSTE Rear kit). System is equipped with Tru-Earth Leveling™.			X
					228								FS80F53S3-DSTE 8000	Front Suspension (requires DS150F53S3-DSTE or DS150F53S3TE Rear kit). Double Stack Front Volumes in-board at front. System is equipped with Tru-Earth Leveling™.			X
FRONT F53 22K GVW	2020+	8000	n/a	n/a	208	n/a	n/a	n/a	n/a	n/a	Steel Leaf 8000	No	FS80F53S3TE 8000	Front Suspension (requires DS150F53S3TE or DS150F53S3-DSTE Rear kit). System is equipped with Tru-Earth Leveling™.			X
					242								FS80F53S3-DSTE 8000	Front Suspension (requires DS150F53S3-DSTE or DS150F53S3TE Rear kit). Double Stack Front Volumes in-board at front. System is equipped with Tru-Earth Leveling™.			X
FRONT F53 24K GVW	2020+	9000	n/a	n/a	228	n/a	n/a	n/a	n/a	n/a	Steel Leaf 9000	No	FS90F53S3TE 9000	Front Suspension (requires DS175F53S3TE or DS175F53S3-DSTE Rear kit). System is equipped with Tru-Earth Leveling.			X
					252								FS90F53S3-DSTE 9000	Front Suspension (requires DS175F53S3-DSTE or DS175F53S3TE Rear kit). Double Stack Front Volumes in-board at front. System is equipped with Tru-Earth Leveling.			X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
FRONT F53 26K GVW	2020+	9000	n/a	n/a	228 242 252	n/a	n/a	n/a	n/a	n/a	Steel Leaf 9000	No	FS90F53S3TE 9000	Front Suspension (requires DS175F53S3TE or DS175F53S3-DSTE Rear kit). System is equipped with Tru-Earth Leveling.			X
													FS90F53S3-DSTE 9000	Front Suspension (requires DS175F53S3-DSTE or DS175F53S3TE Rear kit). Double Stack Front Volumes in-board at front. System is equipped with Tru-Earth Leveling.			X
REAR F53 16K GVW	2009-2019	11000	Dana 80	n/a	158 178 190	n/a	n/a	n/a	n/a	n/a	Steel Leaf 11000	No	DS120F53S2TE 12000	(Requires FS70F53S2TE Front kit). 158" WB requires 11468 to mount PM aft of fuel tank. System is equipped with Tru-Earth Leveling.			X
													DS120F53S2-DSTE 12000	(Requires FS70F53S2-DSTE Front kit) Double Stack Rear Volumes aft of fuel tank. PM aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
REAR F53 18K GVW	2009-2019	12000	Dana 80	n/a	178 190 208	n/a	n/a	n/a	n/a	n/a	Steel Leaf 12000	No	DS120F53S2TE 12000	(Requires FS70F53S2TE Front kit) System is equipped with Tru-Earth Leveling™.			X
													DS120F53S2-DSTE 12000	(Requires FS70F53S2-DSTE Front kit) Double Stack Rear Volumes aft of fuel tank. PM aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
REAR F53 20.5K GVW	2009-2019	13500	Dana S110	n/a	208 228	n/a	n/a	n/a	n/a	n/a	Steel Leaf 13500	No	DS150F53S2TE 15000	(Requires FS80F53S2TE or FS80F53S2-DSTE Front kit) System is equipped with Tru-Earth Leveling™.			X
													DS150F53S2-DSTE 15000	(Requires FS80F53S2-DSTE or FS80F53S2TE Front kit) Double Stack Rear Volumes aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
REAR F53 22K GVW	2009-2019	15000	Dana S130	n/a	208 228 242	n/a	n/a	n/a	n/a	n/a	Steel Leaf 15000	No	DS150F53S2TE 15000	(Requires FS80F53S2TE or FS80F53S2-DSTE Front kit) System is equipped with Tru-Earth Leveling™.			X
													DS150F53S2-DSTE 15000	(Requires FS80F53S2-DSTE or FS80F53S2TE Front kit) Double Stack Rear Volumes aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
REAR F53 24K GVW	2009-2019	15500	Dana 17060S	n/a	228 242 252	n/a	n/a	n/a	n/a	n/a	Steel Leaf 15500	No	DS175F53S2TE 17500	(Requires FS90F53S2TE or FS90F53S2-DSTE Front kit) System is equipped with Tru-Earth Leveling™.			X
													DS175F53S2-DSTE 17500	(Requires FS90F53S2-DSTE or FS90F53S2TE Front kit) Double Stack Rear Volumes aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
REAR F53 26K GVW	2009-2019	17500	Dana 17060S	n/a	228 242 252	n/a	n/a	n/a	n/a	n/a	Steel Leaf 17500	No	DS175F53S2TE 17500	(Requires FS90F53S2TE or FS90F53S2-DSTE Front kit) System is equipped with Tru-Earth Leveling™.			X
													DS175F53S3-DSTE 17500	(Requires FS90F53S2-DSTE or FS90F53S2TE Front kit) Double Stack Rear Volumes aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
REAR F53 16K GVW	2020+	11000	Dana S110	n/a	158 178 190	n/a	n/a	n/a	n/a	n/a	Steel Leaf 11000	No	DS120F53S3TE 12000	(Requires FS70F53S3TE Front kit). System is equipped with Tru-Earth Leveling™. 158" WB requires 11468 to mount PM in rear.			X
													DS120F53S3-DSTE 12000	(Requires FS70F53S3-DSTE Front kit) Double Stack Rear Volumes & PM aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
REAR F53 18K GVW	2020+	12000	Dana S110	n/a	178 190 208	n/a	n/a	n/a	n/a	n/a	Steel Leaf 12000	No	DS120F53S3TE 12000	(Requires FS70F53S3TE Front kit). System is equipped with Tru-Earth Leveling™.			X
													DS120F53S3-DSTE 12000	(Requires FS70F53S3-DSTE Front kit) Double Stack Rear Volumes & PM aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
REAR F53 20.5K GVW	2020+	13500	Dana S130	n/a	208 228	n/a	n/a	n/a	n/a	n/a	Steel Leaf 13500	No	DS150F53S3TE 15000	(Requires FS80F53S3TE or FS80F53S3-DSTE Front kit) System is equipped with Tru-Earth Leveling™.			X
													DS150F53S3-DSTE 15000	(Requires FS80F53S3-DSTE or FS80F53S3TE Front kit) Double Stack Rear Volumes aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
REAR F53 22K GVW	2020+	15000	Dana S130	n/a	208 228 242	n/a	n/a	n/a	n/a	n/a	Steel Leaf 15000	No	DS150F53S3TE 15000	(Requires FS80F53S3TE or FS80F53S3-DSTE Front kit) System is equipped with Tru-Earth Leveling™.			X
													DS150F53S3-DSTE 15000	(Requires FS80F53S3-DSTE or FS80F53S3TE Front kit) Double Stack Rear Volumes aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X
REAR F53 24K GVW	2020+	15500	Dana S140	n/a	228 242 252	n/a	n/a	n/a	n/a	n/a	Steel Leaf 15500	No	DS175F53S3TE 17500	(Requires FS90F53S3TE or FS90F53S3-DSTE Front kit) System is equipped with Tru-Earth Leveling™.			X
													DS175F53S3-DSTE 17500	(Requires FS90F53S3-DSTE or FS90F53S3TE Front kit) Double Stack Rear Volumes aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
REAR F53 26K GVW	2020+	17500	Dana S140	n/a	228 242 252	n/a	n/a	n/a	n/a	n/a	Steel Leaf 17500	No	DS175F53S3TE 17500	(Requires FS90F53S3TE or FS90F53S3-DSTE Front kit) System is equipped with Tru-Earth Leveling™.			X
													DS175F53S3-DSTE 17500	(Requires FS90F53S3-DSTE or FS90F53S3TE Front kit) Double Stack Rear Volumes aft of fuel tank. System is equipped with Tru-Earth Leveling™.			X

**Freightliner**

REAR M2	2012-Current	Up to 15000 (15000)		Any	n/a	84+		Cummins Detroit Diesel	Any	Hydraulic***		Yes	DS150FR-SSA 15000	Volumes forward, PM behind rear axle. ** Kit 11337 needed with DA RS 15.0-2 axle. Kit created for Braun (other ambulance mfr can use). Has 10830-013 volume mounts in place of 10830-015. *** Air brakes can be used if s-cams and s-cam tubes are converted to air ride compatible versions. <b>NOTE: 216"WB+ chassis requires 12507-001 &amp; 12508-001 extension harnesses.</b>		X		
	2012-Current	Up to 15000 (15000)	Meritor: MS-17-14X Detroit: RS-17.5-4 RS-17.5-2 RS-15.0-2**	Any	n/a	84+	546-020 546-021 546-094	Cummins Detroit Diesel	Forward Only	Air Drum, Hydraulic	Air Susp: 622-1CW (10K) 622-1CX (12K) 622-1CY (15K)	Yes (hyd brks)	DS150FR-A 15000	Volumes and PM behind rear axle. ** Kit 11338 needed with DA RS 15.0-2 axle <b>NOTE: 216"WB+ chassis requires 12507-001 &amp; 12508-001 extension harnesses.</b>	X	X	X	X
	2012-Current	Up to 15000 (15000)		Any	n/a	84+	546-093 546-099 546-100	Cummins Detroit Diesel	Any	Air Drum, Hydraulic		Yes (hyd)	DS150FR-AS 15000	Volumes forward and PM behind rear axle. ** Kit 11338 needed with DA RS 15.0-2 axle <b>NOTE: 216"WB+ chassis requires 12507-001 &amp; 12508-001 extension harnesses.</b>	X	X	X	X
	2012-Current	Up to 15000 (15000)		Any	n/a	84+	546-120 546-122 546-1AG	Cummins Detroit Diesel	Any	Air Drum, Hydraulic		Yes (hyd brks)	DS150FR-ASA 15000	Volumes forward, PM behind rear axle. ** Kit 11338 needed with DA RS 15.0-2 axle. Kit created for Braun (other ambulance mfr can use). Has 10830-013 volume mounts in place of 10830-015. <b>NOTE: 216"WB+ chassis requires 12507-001 &amp; 12508-001 extension harnesses.</b>		X		

**Freightliner Custom Chassis**

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application			
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle	
REAR S2C	2012-Current	Up to 15000	Mentor: MS-17-14X	Any	n/a	84+	n/a	Cummins Detroit Diesel	Rear	Air Drum, Hydraulic	23K Airliner	No	DS150FRC-A23 15000	Volumes and PM forward LH inside frame. Designed for 22.5" tires	X		X	X
	2012-Current	Up to 17500	Mentor: MS-17-14X	Any	n/a	84+	n/a	Cummins Detroit Diesel	Rear	Air Drum, Hydraulic	23K Airliner	No	DS175FRC-A23 17500	Volumes and PM forward LH inside frame. Designed for 22.5" tires	X		X	X

**General Motors (Chevrolet/GMC)**

**Express/Savana G-Series Cutaway**

FRONT G3500 G4500	2013- Current	4600	n/a	Cutaway	139, 159, 177	80, 100, 118	n/a	Gas	Rear	n/a	n/a	No	FS46GM 4600	Front Suspension (requires Rear DS96GM5-AR kit) Double Stack Volumes on Driver Side Frame Rail		X	X
													FS46GM-SS 4600	Front Suspension (requires Rear DS96GM5-AR kit) Split Stack Volumes		X	X
FRONT G4500 based Low Floor bus (Arboc)	2013- Current	4600	n/a	Cutaway	165, 191, 210	n/a	n/a	Gas	Rear	n/a	n/a	No	FS46GM-SOA 4600	Front Suspension (requires Rear DS96GM5-SOA/-SOASB kit) <b>Note: requires Frame Drilling Template Kit p/n: 12306</b> <b>**Special unit for Arboc</b>			X
REAR G3500: G33503 G33803 G33903	2013-Current	8600	n/a	Cutaway	139, 159, 177	80, 100, 118	n/a	Gas	Midship	n/a	n/a	No	DS96GM5-AM 9600	PM rear mount, Includes Intermotive UIM for speed.	X	X	X
	2013-Current	8600	n/a	Cutaway	139, 159, 177	80, 100, 118	n/a	Gas	Rear	n/a	n/a	No	DS96GM5-AR 9600	PM forward, LH inside frame, Includes Intermotive UIM for speed.	X	X	X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
REAR G4500: G33803 G33903	2013-Current	9600	n/a	Cutaway	139, 159, 177	80, 100, 118	n/a	Gas	Midship	n/a	n/a	No	DS96GM5-AM 9600	PM rear mount, Includes Intermotive UIM for speed.	X	X	X
	2013-Current	9600	n/a	Cutaway	139, 159, 177	80, 100, 118	n/a	Gas	Rear	n/a	n/a	No	DS96GM5-AR 9600	PM forward, LH inside frame, Includes Intermotive UIM for speed.	X	X	X
REAR G4500 based Low Floor bus	2013-Current	9600	n/a	Cutaway	191 210	n/a	n/a	Gas	Rear	n/a	n/a	No	DS96GM5-ASF 9600	PM forward, LH inside frame, Volumes mounted high and outboard from frame. Includes Intermotive UIM for speed. ** Special unit for Arboc.			X
													DS96GM5-SOA 9600	PM forward, LH inside frame, Volumes mounted high and outboard from frame. Includes Intermotive UIM for speed. (Requires FS46GM-SOA Front Kit). ** Special unit for Arboc			X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

																Application		
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
(Arboc)													DS96GM5-ASF5B 9600	PM forward, LH inside frame, Volumes mounted high and outboard from frame, short wheelbase.			X	
					165	n/a	n/a	Gas	Rear	n/a	n/a	No	DS96GM5-SOASB 9600	PM forward, LH inside frame, Volumes mounted high and outboard from frame, short wheelbase. Includes Intermotive UIM for speed. (Requires FS46GM-SOA Front Kit). ** Special unit for Arboc			X	
<b>Silverado/Sierra Cab Chassis</b>																		
REAR C/K 3500HD: C/K 36403/31403	2020-Current	10500	*Wide Track	Reg	171	84.5	n/a	Gas	Any	n/a	n/a	TBD	DS105GM2 10500	*Requires GTY wide track rear axle; Midship delete with diesel, DEF relocation inside framerail only.	X	X		
	2020-Current	10500	*Wide Track	Reg	171	84.5	n/a	Gas	Any	n/a	n/a	TBD	DS105GM2F 10500	*Requires GTY wide track rear axle; Midship delete with diesel, DEF relocation inside framerail only; PM mounted behind rear tank	X	X		
<b>Silverado Cab Chassis Medium Duty</b>																		
REAR 4500HD 4x2 (15K-16.5K GVW)	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV2-S 13500	4x2 only; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K IROS Air Ride	Yes	DS135NCV2-A 13500	4x2 only; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV2-SF 13500	4x2 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K IROS Air Ride	Yes	DS135NCV2-AF 13500	4x2 only; Vol. split along frame rails; Rear PM; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X		
REAR 4500HD 4x4 (15K-16.5K)	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV4-S 13500	4x4 only; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV4-SF 13500	4x4 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X		
REAR 5500HD 4x2 (17.5-19.5K GVW)	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV2-S 13500	4x2 only; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K IROS Air Ride	Yes	DS135NCV2-A 13500	4x2 only; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV2-SF 13500	4x2 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K IROS Air Ride	Yes	DS135NCV2-AF 13500	4x2 only; Vol. split along frame rails; Rear PM; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X		
	2019-Current	15000-15500	S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV2-S 15500	4x2 only; <b>No S140 axle</b>		X		
2019-Current	15000-15500	S16-130	Reg, Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	15K-15.5K IROS Air Ride	Yes	DS155NCV2-A 15500	4x2 only; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X			

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV2-SF 15500	4x2 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X	
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K IROS Air Ride	Yes	DS155NCV2-AF 15500	4x2 only; Vol. split along frame rails; Rear PM; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X	
REAR 5500HD 4x4 (17.5-19.5K GVW)	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV4-S 13500	4x4 only; <b>No S140 axle</b>		X	
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV4-SF 13500	4x4 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X	
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV4-S 15500	4x4 only; <b>No S140 axle</b>		X	
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV4-SF 15500	4x4 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X	
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV4-SM 15500	Vol. double stacked pass. side; PM at rear; May require 12156 compartment mod kit; <b>No S140 axle</b>			X
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV2-S 13500	4x2 only; <b>No S140 axle</b>		X	
REAR 6500HD 4x2 (21K-22.94K GVW)	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K IROS Air Ride	Yes	DS135NCV2-A 13500	4x2 only; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X	
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV2-SF 13500	4x2 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X	
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K IROS Air Ride	Yes	DS135NCV2-AF 13500	4x2 only; Vol. split along frame rails; Rear PM; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X	
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV2-S 15500	4x2 only; <b>No S140 axle</b>		X	
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	15K-15.5K IROS Air Ride	Yes	DS155NCV2-A 15500	4x2 only; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X	
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV2-SF 15500	4x2 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X	
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K IROS Air Ride	Yes	DS155NCV2-AF 15500	4x2 only; Vol. split along frame rails; Rear PM; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X	
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV4-S 13500	4x4 only; <b>No S140 axle</b>		X	
REAR 6500HD 4x4 (21K-22.94K)	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV4-SF 13500	4x4 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X	
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV4-S 15500	4x4 only; <b>No S140 axle</b>		X	

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

														Application				
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
GVW)	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV4-SF 15500	4x4 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV4-SM 15500	Vol. double stacked pass. side; PM at rear; May require 12156 compartment mod kit; <b>No S140 axle</b>				X
<b>General Motors (Chevrolet/GMC) -- TSC Install (Only Available at Chevrolet/GMC Dealers)</b>																		
<b>Silverado Cab Chassis Medium Duty -- TCS Ship-Thru Code: WU2</b>																		
REAR 4500HD 5500HD 6500HD 4x2 (15K-22.94K GVW)	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 189" (ER2)	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS135NCV2-NV6 13500	Chevrolet Order Code: 91C (13.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM located behind axle; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 189" (ER2)	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS135NCV2-NSTV6 13500	Chevrolet Order Code: 91B (13.5K LiquidSpring Accommodation Pkg) Volumes each side, PM located behind axle; <b>No S140 axle</b>		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 189" (ER2)	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS155NCV2-NV6 15500	Chevrolet Order Code: 91E (15.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM located behind axle; <b>No S140 axle</b>		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 189" (ER2)	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS155NCV2-NSTV6 15500	Chevrolet Order Code: 91D (15.5K LiquidSpring Accommodation Pkg) Volumes each side, PM located behind axle; <b>No S140 axle</b>		X		
REAR 4500HD 5500HD 6500HD 4x4 (15K-22.94K GVW)	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 189" (ER2)	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS135NCV4-NV6 13500	Chevrolet Order Code: 91C (13.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM located behind axle; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 189" (ER2)	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS135NCV4-NSTV6 13500	Chevrolet Order Code: 91B (13.5K LiquidSpring Accommodation Pkg) Volumes each side, PM located behind axle; <b>No S140 axle</b>		X		

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

														Application				
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
15K-22.5K GVW	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 189"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS155NCV4-NV6 15500	Chevrolet Order Code: 91E (15.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side. PM located		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 189"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS155NCV4-NSTV6 15500	Chevrolet Order Code: 91D (15.5K LiquidSpring Accommodation Pkg)		X		
<b>International (Navistar) -- See next section for CBC/TSC Installations Available</b>																		
<b>CV (see next section for TSC Installations available)</b>																		
REAR CV 4x2	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV2-S 13500	4x2 only; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K IROS Air Ride	Yes	DS135NCV2-A 13500	4x2 only; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV2-SF 13500	4x2 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K IROS Air Ride	Yes	DS135NCV2-AF 13500	4x2 only; Vol. split along frame rails; Rear PM; 2021+ requires calibration file update at GM dealer for		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV2-S 15500	4x2 only; <b>No S140 axle</b>		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	15K-15.5K IROS Air Ride	Yes	DS155NCV2-A 15500	4x2 only; 2021+ requires calibration file update at GM dealer for Stabilitrak option; <b>No S140 axle</b>		X		
REAR CV 4x4	2019-Current	10000-13500	S14-110	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV4-S 13500	4x4 only; <b>No S140 axle</b>		X		
	2019-Current	10000-13500	S14-110	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	10K-13.5K Steel Leaf	Yes	DS135NCV4-SF 13500	4x4 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV4-S 15500	4x4 only; <b>No S140 axle</b>		X		

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application			
															Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV4-SF 15500	4x4 only; Vol. split along frame rails; Rear PM; <b>No S140 axle</b>		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	15K-15.5K Steel Leaf	Yes	DS155NCV4-SM 15500	Vol. double stacked pass. side; PM at rear; May require 12156 compartment mod kit; <b>No S140 axle</b>				X
<b>MV60H LP -- DuraStar 4300/4400 Low Profile (Taper Frame) (see next section for TSC Installations available)</b>																		
<b>REAR MV607</b>  <b>DuraStar 4300/4400 Low Profile</b>	2008-Current	13500-15500 (13500)	Dana S14-130 S16-130	Any	n/a	84+	n/a	Cummins	Any	Hydraulic	10K-13.5K Steel Leaf 14SAC, 14SAE, 14SAH	Yes	DS135ND-S130C 13500	Volumes double stacked LH inboard frame. PM LH below frame. Different speed signal.	X	X	X	X
	2008-Current	13500-15500 (13500)	Dana S14-130 S16-130	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	10K-13.5K IROS Air Ride 14TBL, 14TBM, 14TBN	Yes, Hyd. Brk only	DS135ND-A130C 13500	Volumes double stacked LH inboard frame. PM LH below frame. Different speed signal.	X	X	X	X
	2008-Current	13500-17500 (13500)	Dana: S17-140 S19-140 17060S / D 19060S / D Meritor:	Any	n/a	84+	n/a	Cummins	Any	Hydraulic***	10K-13.5K Steel Leaf 14SAC, 14SAE, 14SAH	Yes	DS135ND-SC 13500	Volumes double stacked LH inboard frame. PM LH below frame. Different speed signal. *** Air brakes can be used if s-cams and s-cam tubes are converted to air ride compatible versions.	X	X	X	X
	2008-Current	13500-17500 (13500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	10K-13.5K IROS Air Ride 14TBL, 14TBM, 14TBN	Yes, Hyd. Brk only	DS135NDLP-A 13500	Volumes double stacked LH inboard frame. PM behind axle. Different speed signal. <b>NOTE: Crew Cab chassis requires 12507-001 &amp; 12508-001 extension harnesses.</b>	X	X	X	X
	2008-Current	13500-17500 (15500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	10K-13.5K IROS Air Ride 14TBL, 14TBM, 14TBN	Yes, Hyd. Brk only	DS155NDLP-AA 15500	Volumes are double stacked on driver side; PM behind axle. Different speed signal. <b>NOTE: Crew Cab chassis requires 12507-001 &amp; 12508-001 extension harnesses.</b>	X	X	X	X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application			
															Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
	2008-Current	13500-17500 (15500)	MS-17-14X	Any	n/a	84+	n/a	Cummins	Any	Hydraulic***	10K-13.5K Steel Leaf	Yes	DS155NDLP-SC 15500	Volumes split along frame rails; PM behind axle. Different speed signal.	X	X	X	X
	2008-Current	13500-17500 (15500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	10K-13.5K IROS Air Ride 14TBL, 14TBM, 14TBN	Yes, Hyd. Brk only	DS155NDLP-AST 15500	Volumes split along frame rails; PM behind axle. Different speed signal. <b>NOTE: Crew Cab chassis requires 12507-001 &amp; 12508-001 extension harnesses.</b>	X	X	X	X
<b>MV607 -- DuraStar 4300 Straight Rail (see next section for TSC Installations available)</b>																		
<b>REAR MV607 DuraStar 4300/4400 Straight Rail</b>	2008-Current	13500-21000 (15500)	Dana: S17-140 S19-140 17060S / D 19060S / D Meritor: MS-17-14X MS-19-14X MS-21-14X	Any	n/a	84+	n/a	Cummins	Any	Hydraulic	13.5K-20K Steel Leaf	TBD	DS155NDSR-S 15500	Volumes along side frame rail, PM inside frame on LH side. Max tire width on 8.25" rims is 255 mm, max on 7.5" rims is 295.	X		X	X
	2008-Current	13500-21000 (18500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic	13.5K-20K Steel Leaf	TBD	DS185NDSR-S 18500	Volumes along side frame rail, PM inside frame on LH side. Max tire width on 8.25" rims is 255 mm, max on 7.5" rims is 295.	X		X	X
	2008-Current	13500-21000 (20000)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic	13.5K-20K Steel Leaf	TBD	DS200NDSR-S 20000	Volumes along side frame rail, PM inside frame on LH side. Max tire width on 8.25" rims is 255 mm, max on 7.5" rims is 295.	X		X	X
	2008-Current	13500-21000 (15500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic	13.5K-20K Steel Leaf	TBD	DS155NDSR-SM 15500	Special unit for Nexus motorhome using MV/Durastar. Volumes and PM are located in rear (behind axle). Max tire width on 8.25" rims is 255 mm, max on 7.5" rims is 295.				X
	2008-Current	13500-21000 (15500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic	13.5K-20K Steel Leaf	TBD	DS185NDSR-SM 18500	Special unit for Nexus motorhome using DuraStar "lite". Volumes and PM are located in rear (behind axle). Max tire width on 8.25" rims is 255 mm, max on 7.5" rims is 295.				X
	2008-Current	13500-21000 (15500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	13.5K-20K IROS Air Ride	TBD	DS155NDSR-A 15500	Volumes along side frame rail, PM inside frame on LH side.	X		X	X
	2008-Current	13500-21000 (18500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	13.5K-20K IROS Air Ride	TBD	DS185NDSR-A 18500	Volumes along side frame rail, PM inside frame on LH side. Max tire width on 8.25" rims is 255 mm, max on 7.5" rims is 295.	X		X	X
	2008-Current	13500-21000 (18500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	13.5K-20K IROS Air Ride	TBD	DS185NDSR-AM 18500	Special unit for Nexus motorhome using MV/Durastar. Volumes and PM are located in rear (behind axle). Max tire				X

### LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

														Application				
Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
	2008-Current	13500-21000 (20000)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	13.5K-20K IROS Air Ride	TBD	DS200NDSR-A 20000	Volumes along side frame rail, PM inside frame on LH side. Max tire width on 8.25" rims is 255 mm, max on 7.5" rims is 295.	X		X	X
DuraStar kits include brackets to work with the following steering gearboxes: TRW TAS-40, TRW THP-45, Sheppard M100, Sheppard HD94 (also requires 11136-007 kit). Do not use LiquidSpring suspensions with TRW TAS-66 or TRW THP-60 gearboxes.																		
<b>International (Navistar) -- CBC / TSC Install (Only available at International Dealers)</b>																		
<b>CV -- TSC Install</b>																		
<b>Rear CV 4x2</b>	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS135NCV2-NV6 13500	Navistar Order Code: 0014TDR (13.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM behind axle		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	N/A	Yes	DS135NCV2-NSTV6 13500	Navistar Order Code: 0014TDW (13.5K LiquidSpring Accommodation Pkg) Volumes each side, PM behind axle		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS155NCV2-NV6 15500	Navistar Order Code: 0014TDS (15.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM behind axle		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	N/A	Yes	DS155NCV2-NSTV6 15500	Navistar Order Code: 0014TDX (15.5K LiquidSpring Accommodation Pkg) Volumes each side, PM behind axle		X		
<b>Rear CV 4x4</b>	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 189"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS135NCV4-NV6 13500	Navistar Order Code: 0014TDR (13.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM behind axle		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Only 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS135NCV4-NSV6 13500	Navistar Order Code: 0014TDR (13.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM behind axle. 7" pinion angle		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Min. 189"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	N/A	Yes	DS135NCV4-NSTV6 13500	Navistar Order Code: 0014TDW (13.5K LiquidSpring Accommodation Pkg) Volumes each side, PM behind axle		X		
	2019-Current	10000-13500	S14-110 S16-130	Reg. Crew	Only 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	N/A	Yes	DS135NCV4-NSTVS 13500	Navistar Order Code: 0014TDW (13.5K LiquidSpring Accommodation Pkg) Volumes each side, PM behind axle. 7" pinion angle		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 189"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS155NCV4-NV6 15500	Navistar Order Code: 0014TDS (15.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM behind axle		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Only 165"	84, 108	n/a	Gas, Diesel	Rear	Hydraulic Only	N/A	Yes	DS155NCV4-NSV6 15500	Navistar Order Code: 0014TDS (15.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM located behind axle. 7" pinion angle		X		

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application			
															Adventure Truck	EMS, Fire and Rescue Vehicles	Mobility	Recreational Vehicle
	2019-Current	15000-15500	S16-130	Reg. Crew	Min. 189"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	N/A	Yes	DS155NCV4-NSTV6 15500	Navistar Order Code: 0014TDX (15.5K LiquidSpring Accommodation Pkg)		X		
	2019-Current	15000-15500	S16-130	Reg. Crew	Only 165"	84, 108	n/a	Gas, Diesel	Rear/Midship	Hydraulic Only	N/A	Yes	DS155NCV4-NSTV6 15500	Navistar Order Code: 0014TDX (15.5K LiquidSpring Accommodation Pkg) Volumes each side, PM behind axle. 7° pinion angle		X		
<b>MV60H LP -- DuraStar 4300/4400 Low Profile (Taper Frame) -- TSC Install</b>																		
<b>REAR MV60H-LP Low Profile Tapered Frame</b>	2019-Current	13500-15500 (13500)	Dana S14-130 S16-130	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS135NDLP-N2V6 13500	Navistar Order Code: 0014TDR (13.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM located behind axle (Axle triggers unit change)	X	X	X	X
	2019-Current	13500-15500 (13500)	Dana S14-130 S16-130	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS135NDLP-N5V6 13500	Navistar Order Code: 0014TDW (13.5K LiquidSpring Accommodation Pkg) Volumes are split between LH and RH side, PM located behind axle, short wheelbase (Axle triggers unit change)	X	X	X	X
	2019-Current	13500-15500 (13500)	Dana S14-130 S16-130	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS135NDLP-N6V6 13500	Navistar Order Code: 0014TDW (13.5K LiquidSpring Accommodation Pkg) Volumes are split between LH and RH side, PM located behind axle, long wheelbase (Axle triggers unit change)	X	X	X	X
	2019-Current	13500-15500 (15500)	Dana S14-130 S16-130	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS155NDLP-N2V6 15500	Navistar Order Code: 0014TDS (15.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM located behind axle (Axle triggers unit change)	X	X	X	X
	2019-Current	13500-15500 (15500)	Dana S14-130 S16-130	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS155NDLP-N5V6 15500	Navistar Order Code: 0014TDX (15.5K LiquidSpring Accommodation Pkg) Volumes are split between LH and RH side, PM located behind axle, short wheelbase (Axle triggers unit change)	X	X	X	X
	2019-Current	13500-15500 (15500)	Dana S14-130 S16-130	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS155NDLP-N6V6 15500	Navistar Order Code: 0014TDX (15.5K LiquidSpring Accommodation Pkg) Volumes are split between LH and RH side, PM located behind axle, long wheelbase (Axle triggers unit change)	X	X	X	X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application			
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle	
<b>REAR MV60H-LP Low Profile Tapered Frame</b>	2019-Current	13500-17500 (13500)	Dana: S17-140 S19-140 17060S / D Meritor: MS-17-14X	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS135NDLP-N1V6 13500	Navistar Order Code: 0014TDR (13.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM located behind axle (Axle triggers unit change)	X	X	X	X
	2019-Current	13500-17500 (13500)	Dana: S17-140 S19-140 17060S / D Meritor: MS-17-14X	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS135NDLP-N3V6 13500	Navistar Order Code: 0014TDW (13.5K LiquidSpring Accommodation Pkg) Volumes are split between LH and RH side, PM located behind axle, short wheelbase (Axle triggers unit change)	X	X	X	X
	2019-Current	13500-17500 (13500)	Dana: S17-140 S19-140 17060S / D Meritor: MS-17-14X	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS135NDLP-N4V6 13500	Navistar Order Code: 0014TDW (13.5K LiquidSpring Accommodation Pkg) Volumes are split between LH and RH side, PM located behind axle, long wheelbase (Axle triggers unit change)	X	X	X	X
	2019-Current	13500-17500 (15500)	Dana: S17-140 S19-140 17060S / D Meritor: MS-17-14X	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS155NDLP-N1V6 15500	Navistar Order Code: 0014TDS (15.5K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM located behind axle (Axle triggers unit change)	X	X	X	X
	2019-Current	13500-17500 (15500)	Dana: S17-140	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd.	DS155NDLP-N3V6 15500	Navistar Order Code: 0014TDX (15.5K LiquidSpring Accommodation Pkg)	X	X	X	X
	2019-Current	13500-17500 (15500)	Dana: S17-140 S19-140 17060S / D Meritor: MS-17-14X	Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	Yes, Hyd. Brk only	DS155NDLP-N4V6 15500	Navistar Order Code: 0014TDX (15.5K LiquidSpring Accommodation Pkg) Volumes are split between LH and RH side, PM located behind axle, long wheelbase (Axle triggers unit change)	X	X	X	X
<b>IC Bus (CE School and Commercial) -- CBC Install</b>																		
	2019-Current	13500-21000 (18500)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	TBD	DS185NDSR-NBV6 18500	Navistar Order Code: 0014TEA (18.5K LiquidSpring Accommodation Pkg)			X	

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
	2019-Current	13500-21000 (21000)		Any	n/a	84+	n/a	Cummins	Any	Hydraulic or Air	N/A	TBD	DS210NDSR-NBV6 21000	Navistar Order Code: 0014TDZ (21K LiquidSpring Accommodation Pkg) Volumes double stacked on driver side, PM located behind axle			X

Use the following kits for Steering Gearboxes on CBC/TSC MV and IC Bus units: 11596 Sheppard M1100; 11599 TAS 40; 11600 THP 45; 11601 Sheppard HD94

**Ram**

**3500 Pickup 2" Lift Kit**

Front 3500 SRW Pickup	2024+	5500 - 6000	n/a	CC MC	149.4 160.5	n/a	n/a	Any	Standard	n/a	n/a	No	FS60RP-L2 6000	4x4 & Short Bed Only. Volumes mounted split stack on frame rail. Requires DS70RP-L2DSTE or DS98RP-L2DSTE rear. <b>Equipped with Tru-Earth Leveling™.</b>	X		
													FS60RP-L2E <sup>1</sup> 6000		X		
Rear 3500 SRW Pickup	2024	7000	SRW	CC MC	149.4 160.5	n/a	n/a	Any	Standard	n/a	n/a	No	DS70RP-L2DS 7000	REQUIRES 5TH WHEEL HITCH; 4x4 & Short Bed Only. Removes spare tire. Volumes & power module mounted behind rear axle. Air bag system removed if equipped. <b>Equipped with Tru-Earth Leveling™.</b>	X		
													DS70RP-L2DSE <sup>1</sup> 7000		X		
	2025+												DS70RS2P-L2DS 7000	REQUIRES 5TH WHEEL HITCH; REQUIRES VSIM; 4x4 & Short Bed Only. Removes spare tire. Volumes & power module mounted behind rear axle. Air bag system removed if equipped. <b>Equipped with Tru-Earth Leveling™.</b>	X		
													DS70RS2P-L2DSE <sup>1</sup> 7000		X		
Rear 3500 DRW Pickup	2024	9750	DRW	CC MC	149.4 160.5	n/a	n/a	Any	Standard	n/a	n/a	No	DS98RP-L2DS 9750	REQUIRES 5TH WHEEL HITCH; 4x4 & Short Bed Only. Removes spare tire. Volumes & power module mounted behind rear axle. Air bag system removed if equipped. <b>Equipped with Tru-Earth Leveling™.</b>	X		
													DS98RP-L2DSE <sup>1</sup> 9750		X		
	2025+												DS98RS2P-L2DSE 9750	REQUIRES 5TH WHEEL HITCH; REQUIRES VSIM; 4x4 & Short Bed Only. Removes spare tire. Volumes & power module mounted behind rear axle. Air bag system removed if equipped. <b>Equipped with Tru-Earth Leveling™.</b>	X		
													DS98RS2P-L2DSE <sup>1</sup> 9750		X		

**3500 Cab Chassis**

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
<b>REAR 3500 Cab</b>	2019-Current	9850	n/a	Reg	168	84	n/a	Any	Mid, Rear	n/a	n/a	Yes	DS99RS3 9850	Must include the XXS VSIM option (included in ambulance prep)	X	X	
<sup>1</sup> International export models have 0 psi precharge accumulators																	
<b>4500 Cab Chassis Stock Height</b>																	
<b>FRONT 4500 Cab Chassis</b>	2014-Current	7000	n/a	Reg, Reg, CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	n/a	No	FS70RA 7000 (FS70RAC)	Front Suspension (requires Rear DS135RS2A/RS3A/RS4-A kit) FS70RAC includes FS70RA and conversion kits for existing vehicles with DS135RS2A/RS3A/RS4-A installed.	X	X	
	2014-Current	7000	n/a	Reg, Reg, CC	169 193 205	84 108 120	n/a	Any	Mid, Rear	n/a	n/a	No	FS70RATE 7000	Front Suspension (requires Rear DS135RS4-ATE kit). System is equipped with Tru-Earth Leveling™.	X	X	
	2014-Current	7000	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	n/a	No	FS70RF 7000 (FS70REC)	Front Suspension (requires Rear DS135RS2AF, DS135RS3/AF/AF60, or DS135RS4-AF/-AF60 kit) FS70REC includes FS70RE and conversion kits for existing	X	X	
	2014-Current	7000	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	n/a	No	FS70RFTE 7000	Front Suspension (requires Rear DS135RS4-L4FWTE/-L4MTE/-L4MBTE kit). System is equipped with Tru-Earth Leveling™.	X	X	
<b>REAR 4500 Cab Chassis</b>	2014-Current	10000	n/a	CC	173	60	n/a	Any	Mid Only	n/a	n/a	Yes	DS100RS4-P 10000	EOG Only. Must include the XXS VSIM option (included in ambulance prep). Requires exhaust PN 68261138AB.			
	2014-Current	11200	n/a	Reg, Reg, CC	169 193 205 197	84 108 120 84	n/a	Any	Rear	n/a	n/a	Yes	DS112RS4-A 11200	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side. PM inside frame, LH side, behind cab.	X	X	X
	2014-Current	12000	n/a	Reg, Reg, CC	169 193 205	84 108 120	n/a	Any	Rear	n/a	n/a	Yes	DS135RS4-A 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side. PM inside frame, LH side, behind cab.	X	X	X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
	2014-Current	12000	n/a	Reg, Reg.	169 193	84 108	n/a	Any	Mid, Rear	n/a	n/a	Yes	DS135RS4-AF 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes outside frame rails, each side. PM under	X	X	X
	2014-Current	12000	n/a	Any	145+	60"+	n/a	Any	Rear Only	n/a	n/a	Yes	DS135RS4-AF60 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side. PM under cab on RH outboard.	X	X	
<b>5500 Cab Chassis Stock Height</b>																	
<b>FRONT 5500 Cab Chassis</b>	2014-Current	7000	n/a	Reg, Reg, Reg, CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	n/a	No	FS70RA 7000 (FS70RAC)	Front Suspension (requires Rear DS135RS2A/RS3A/RS4-A kit) FS70RAC includes FS70RA and conversion kits for existing vehicles with DS135RS2A/RS3A/RS4-A installed.	X	X	X
	2014-Current	7000	n/a	Reg, Reg, Reg, CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	n/a	No	FS70RATE 7000	Front Suspension (requires Rear DS135RS4-ATE kit). System is equipped with Tru-Earth Leveling™.	X	X	X
	2014-Current	7000	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	n/a	No	FS70RF 7000 (FS70RFC)	Front Suspension (requires Rear DS135RS2AF, DS135RS3/AF/AF60, or DS135RS4-AF/AF60 kit) FS70RFC includes FS70RF and conversion kits for existing vehicles with DS135RS2AF/RS3AF/RS4-AF installed.	X	X	X
	2014-Current	7000	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	n/a	No	FS70RFTE 7000	Front Suspension (requires Rear DS135RS4-L4FWTE/-L4MTE/-L4MBTE kit). System is equipped with Tru-Earth Leveling™.	X	X	X
	2014-Current	7250	n/a	Reg, Reg, Reg, CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	n/a	No	FS73RA 7250	High Capacity Front Suspension (requires Rear DS135RS2/A/-DM kit, DS135RS3/A/-DM kit, or DS135RS4-A)	X	X	X
	2014-Current	7250	n/a	Reg, Reg, Reg, CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	n/a	No	FS73RATE 7250	Front Suspension (requires Rear DS135RS4-ATE kit). System is equipped with Tru-Earth Leveling™.	X	X	X
	2014-Current	7250	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	n/a	No	FS73RF 7250	Front Suspension (requires Rear DS135RS4-AF/AF60/-L2DS/-L2SS/-L4DS/-L4SS/-L4M/-L4MB kit)	X	X	X
	2014-Current	7250	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	n/a	No	FS73RFTE 7250	Front Suspension (requires Rear DS135RS4-L4FWTE/-L4MTE/-L4MBTE kit). System is equipped with Tru-Earth Leveling™.	X	X	X
<b>REAR 5500 Cab Chassis</b>	2014-Current	10000	n/a	CC	173	60	n/a	Any	Mid Only	n/a	n/a	Yes	DS100RS4-P 10000	EOG Only. Must include the XXS VSIM option (included in ambulance prep). Requires exhaust PN 68261138AB.			
	2014-Current	11200	n/a	Reg, Reg, Reg, CC	169 193 205 197	84 108 120 84	n/a	Any	Rear	n/a	n/a	Yes	DS112RS4-A 11200	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side.	X	X	X
	2014-Current	12000 - 13500	n/a	Reg, Reg, Reg, CC	169 193 205 197	84 108 120 84	n/a	Any	Rear	n/a	n/a	Yes	DS135RS4-A 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side.	X	X	X
	2014-Current	12000 - 13500	n/a	Reg, Reg, Reg, CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	n/a	Yes	DS135RS4-AF 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes outside frame rails, each side. If using 22 gallon midship diesel tank, you'll need to order exhaust P/N: 68261138AA	X	X	X

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
	2014-Current	12000 - 13500	n/a	Any	145+	60"+	n/a	Any	Rear Only	n/a	n/a	Yes	DS135RS4-AF60 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side.	X	X	
	2014-Current	12000 - 13500	n/a	CC	173	60	n/a	Any	Mid Only	n/a	n/a	Yes	DS135RS4-P 13500	EOG Only. Must include the XXS VSIM option (included in ambulance prep). Requires exhaust PN 68261138AB.			
<b>4500/5500 Cab Chassis 2" Lift Kits</b>																	
<b>FRONT 4500/5500 Cab Chassis</b>	2019-Current	7000	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	N/A	No	FS70R-L2 7000	Front Suspension (requires Rear DS135RS4-L2DS/-L2SS/-L4DS/-L4SS/-L4M/-L4MB kit)	X		X
	2019-Current	7000	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	N/A	No	FS70R-L2TE 7000	Front Suspension (requires Rear DS135RS4-L4FWTE/-L4MTE/-L4MBTE kit). System is equipped with Tru-Earth Leveling™.	X		X
	2019-Current	7250	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	N/A	No	FS73R-L2 7250	Front Suspension (requires Rear DS135RS4-L2DS/-L2SS/-L4DS/-L4SS/-L4M/-L4MB kit)	X		X
	2019-Current	7250	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	N/A	No	FS73R-L2TE 7250	Front Suspension (requires Rear DS135RS4-L4FWTE/-L4MTE/-L4MBTE kit). System is equipped with Tru-Earth Leveling™.	X		X
	2019-Current	7250	n/a	Any	145+	60+	n/a	Any	Mid, Rear	n/a	N/A	No	FS73R-L2RCTE 7250	Front Suspension (requires Rear DS135RS4-L4FWTE/-L4MTE/-L4MBTE kit). System is equipped with Tru-Earth Leveling™.	X		X
<b>REAR 4500/5500 Cab Chassis</b>	2014-Current	10000	n/a	CC	173	60	n/a	Any	Mid Only	n/a	N/A	Yes	DS100RS4-L2P 10000	EOG Only. Must include the XXS VSIM option (included in ambulance prep) Speed signal for 41" tires. Requires exhaust PN 68261138AB.			
	2014-Current	10000	n/a	Reg Reg Reg CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	N/A	Yes	DS100RS4-L2SS 10000	Must include the XXS VSIM option (included in ambulance prep). Volumes outside frame rails, each side. PM under cab on RH outboard. If using 22 gallon midship diesel tank, you'll need to order exhaust P/N: 68261138AA. 2" lift over standard.	X		
	2014-Current	10000	n/a	Reg Reg Reg CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	N/A	Yes	DS100RS4-L2SSTE 10000	Must include the XXS VSIM option (included in ambulance prep). Volumes outside frame rails, each side. PM under cab on RH outboard. If using 22 gallon midship diesel tank, you'll need to order exhaust P/N: 68261138AA. 2" lift over standard. System is equipped with Tru-Earth Leveling.	X		
	2014-Current	12000 - 13500	n/a	Any	145+	60+	n/a	Any	Rear Only	n/a	N/A	Yes	DS135RS4-L2DS 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side. PM under cab on RH outboard. 2" lift over standard.	X		
	2014-Current	12000 - 13500	n/a	Reg Reg Reg CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	N/A	Yes	DS135RS4-L2SS 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes outside frame rails, each side. PM under cab on RH outboard. If using 22 gallon midship diesel tank, you'll need to order exhaust P/N: 68261138AA. 2" lift over standard.	X		

LiquidSpring Application Guide: Full Line, p/n D11534 Rev KD

Model	Model Years	Axle GAWR (either Axle or Susp) (lbs)	Axle Model(s)	Cab	WB (in)	CA (in)	Frame	Engine	Fuel Tank Location	Brakes	OEM Susp. GAWR Type	Snow Chain Avail?	LiquidSpring Kit / Max Rating (lbs)	Comments	Application		
															Adventure Truck	EMS, Fire and Rescue Vehicles	Recreational Vehicle
	2014-Current	12000 - 13500	n/a	Reg Reg	169 193	84 108	n/a	Any	Mid, Rear	n/a	N/A	Yes	DS135RS4-L2SSTE 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes outside frame rails, each side. PM under cab on RH outboard. If using 22 gallon midship diesel tank, you'll need to order exhaust P/N: 68261138AA. 4" lift over standard. (Brush Truck)	X		
	2014-Current	12000 - 13500	n/a	CC	173	60	n/a	Any	Mid Only	n/a	N/A	Yes	DS135RS4-L2P 13500	EOG Only. Must include the XXS VSIM option (included in ambulance prep) Speed signal for 41" tires. Requires exhaust PN 68261138AB.			
<b>4500/5500 Cab Chassis 4" Lift Kits</b>																	
	2014-Current	10000	n/a	Reg Reg Reg CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	N/A	Yes	DS100RS4-L4SSTE 10000	Must include the XXS VSIM option (included in ambulance prep). Volumes outside frame rails, each side. PM under cab on RH outboard. If using 22 gallon midship diesel tank, you'll need to order exhaust P/N: 68261138AA. 4" lift over standard. System is equipped with Tru-Earth Leveling.	X		
	2014-Current	12000 - 13500	n/a	Any	145+	60"+	n/a	Any	Rear Only	n/a	N/A	Yes	DS135RS4-L4DS 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side. PM under cab on RH outboard. 4" lift over standard. (Brush Truck)	X		
	2014-Current	12000 - 13500	n/a	Reg Reg Reg CC	169 193 205 197	84 108 120 84	n/a	Any	Mid, Rear	n/a	N/A	Yes	DS135RS4-L4SSTE 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes outside frame rails, each side. PM under cab on RH outboard. If using 22 gallon midship diesel tank, you'll need to order exhaust P/N: 68261138AA. 4" lift over standard. System is equipped with Tru-Earth Leveling.	X		
	2014-Current	12000 - 13500	n/a	Any	145+	60"+	n/a	Any	Rear Only	n/a	N/A	Yes	DS135RS4-L4MTE 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side. PM under cab on RH outboard. 4" lift over standard. (Use with Dynamax). System is equipped with Tru-Earth Leveling™.	X		X
	2014-Current	12000 - 13500	n/a	Any	145+	60"+	n/a	Any	Rear Only	n/a	N/A	Yes	DS135RS4-L4MBTE 13500	Must include the XXS VSIM option (included in ambulance prep). Volumes double stacked inside of frame rails, LH side. PM under cab on RH outboard. 4" lift over standard. Speed signal for 41" tires. System is equipped with Tru-Earth Leveling™.	X		X

Revision	Date	By	ECR	Comment
GT	2/13/2025	BAS	EC1885	Added FS60RP-L2TE
GU	2/20/2025	LFM	EC1887	Added FS60FS2P & DS72FS2P-DS and FS60FS4P-L4 & DS72FS2P-L4DS to F350 PU
GW	3/4/2025	BKC	EC1859	Added FS70-75FS3-L4/M/MTE/TE & FS70-75FS4-L4/M/MTE/TE
GY	3/6/2025	HJC	EC1864	Added DS155FS4-L2RTE and DS155FS4-L4RTE
HA	4/2/2025	BKC	EC1900	Added FS60FS4PW-L2 & FS60FS4PW-L4
HB	4/3/2025	LFM	EC1906	Obsoleted (removed) DS100F2, DS100F4, DS100F2F, & DS100F4F
HC	4/10/2025	RBC	EC1898	Added DS103FS2P kits by replacing DS103FP kits
HD	4/11/2025	LFM	EC1908	Removed note to order 12803 kit, now included with DS103F units, for MY2022 & prior F-350 Chassis Cab units.
HE	4/14/2025	BKC	EC1910	Added dual steering stabilizer note to 4" Lift F450/550/600 front suspensions
HF	4/17/2025	LFM	EC1921	Added DS72FS2P-L4DSE export model to Rear F350 PU 4" Lift Kit section
HG	4/17/2025	BKC	EC1922	Added FS60FS3P-L4/E, FS60FS3PW-L2/E, & FS60FS3PW-L4/E
HH	4/23/2025	BKC	EC1918	Added FS60FS2PE, FS60FS4P-L4E, & FS60FS4PW-L2E/-L4E
HJ	4/24/2025	RBC	EC1924	Replaced DS70RP-L2DSTE & DS98RP-L2DSTE w/ DS70RP-L2DS & DS98RP-L2DS
HK	4/28/2025	HJC	EC1927	Added DS85FS3-FR
HL	4/29/2025	HJC	EC1912	Obsoleted (Removed) DS96FS2M
HM	4/29/2025	BKC	EC1929	Added FS75FS2-MTE
HN	4/30/2025	RBC	EC1930	Added DS70RP-L2DSE & DS98RP-L2DSE
HP	4/30/2025	BAS	EC1909	Removed TE from FS60RP-L2TE and Added FS60RP-L2E
HR	5/7/2025	BKC	EC1934	Added FS60FS3P-L2/E & FS60FS4P-L2/E
HT	5/8/2025	HJC	EC1933	Added DS103F4-DS60D
HU	5/9/2025	RBC	EC1932	Added DS63FS2P-DS/-SS/-L2DS/-L2SS/-L4DS/-L4DSE
HV	5/22/2025	RBC	EC1945	Added DS72FS2P-SS/-L2DS/-L2SS; Removed DS72FP-DS/-SS/-L2DS/-L2SS/-L4DS
HW	5/29/2025	BKC	EC1950	Added FS60FS2PW/E
HY	5/30/2025	CJH	EC1947	Release DS155NDLP-AA
JA	6/5/2025	RBC	EC1956	Obsoleted DS135RS4-L4FWTE; Removed DS100-135RS4-L4SS that was missed on EC1814
JB	6/9/2025	BKC	EC1955	Added FS70-75FS3-L2/M/MTE/TE & FS70-75FS4-L2/M/MTE/TE
JC	6/9/2025	RBC	EC1954	Added DS70-98RS2P-L2DS/-L2DSE kits
JD	6/11/2025	LFM	EC1962	Obsoleted FS60FPW; FS60FP Axle Model now Std. Track
JE	7/3/2025	RBC	EC1975	Added already released DS96FS3-ASM
JF	7/9/2025	BAS	EC1972	Replaced DS155NDLP-AC with -AST
JG	7/16/2025	RBC	EC1988	Removed note about higher performing leveling system for DS96GM5-SOA & -SOASB
JH	7/24/2025	RBC	EC1993	Removed note about higher performing leveling system for DS96FS3T & DS96FS3-EC
JJ	7/31/2025	RBC	EC1990	Updated note for DS96FS3-CLF
JK	8/13/2025	HJC	EC2013	Added DS112RS4-A
JL	8/15/2025	BAS	EC2008	Added DS155FS4-L2DRTE/-L4DRTE
JM	8/18/2025	BKC	EC2014	Removed DS85FS2/-BA & DS96FS2/-BA
JN	9/3/2025	LFM	EC1964 & EC1981	EC1964: Added FS70/80/90F53S2-DSTE & FS70/80/90F53S3-DSTE EC1981: Added DS120/150/175F53S2-DSTE & DS120/150/175F53S3-DSTE
JP	9/4/2025	CJH	EC2018	Release DS100FS4-L4DSD
JR	9/26/2025	CJH	EC1938	Release FS73R-L2RC
JT	10/30/2025	LFM	EC2031	Added 546-1AG to frames allowed for DS150FR-A/-AS/-ASA
JU	12/1/2025	LFM	EC2040	Added 546-120 & 546-122 to frames allowed for DS150FR-A/-AS/-ASA
JV	12/10/2025	CJH	EC2046	Obsolete DS135N-A
JW	12/18/2025	BKC	EC2022	Added DS103FS2P-L2DSE
JY	1/15/2026	BKC	EC2058	Added FS95FS4-L4AV
KA	1/15/2026	CJH	EC2059	EC2059: Added DS155FS4-L4AV
KB	1/16/2026	KZT	EC2060	Added DS72FS2P-DSE
KC	1/29/2026	LFM	EC2036	Added 1325 Kit requirement comment to Front F350 Chassis Cab 4x4 FS60FP with DS103F4F
KD	2/12/2026	HJC	EC2078	Added DS103FS2P-L4SS to F350 PU 4" Lift and F450 PU 4" Lift